

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS

Motor type: 7CV2164C SIMOTICS SD - 160L - IM B3 - 6 p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data Safe Area

U	Δ / Y	f	P	P	I	n	M	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL	
[V]±10%		[Hz]±5%	[kW]	[hp]	[A]	[1/min]	[kgf.m]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4					
Motordaten / Motor Data																			
415	Δ	50	11.00	-/-	22.00	970	11.0	108.0	88.9	88.9	88.6	0.78	0.73	0.62	6.0	2.5	2.6	IE2	
IM B3 / IM 1001			FS 160L		106 kg		SF:1		IS 12615 / IEC 60034-1			-							
Environmental conditions : -20 °C - +50 °C / 1,000 m										Locked rotor time (hot / cold) : 13 s 22 s									

Mechanical data

Sound pressure level 50Hz 60Hz	63 dB(A) 66 dB(A)	External earthing terminal	Yes (standard)
Moment of inertia Rotor GD ²	0.1404 kg m ² 0.5618 kgf.m ²	Vibration severity grade	A (Standard)
Bearing DE NDE	6309 2Z C3 6309 2Z C3	Insulation	155(F) utilized to 130(B)
bearing lifetime		Duty type	S1
L _{10mh} F _{Rad max} according catalogue 50 60Hz ¹⁾	20,000 h 16,000 h	Direction of rotation	Bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	50,000 h 40,000 h	Frame material	Cast iron
Type of bearing	Locating (fixed) bearing, NDE	Forced ventilation motor details	- / -
Relubrication interval/quantity DE NDE	-/- g -/- g -/- h	Net weight of the motor (IM B3)	106 kg
Type of construction	IM B3 / IM 1001	Rotor weight	41 kg
Degree of protection	IP55	Data of anti condensation heating	-/- V, -/- W
Lubricants	Esso Unirex N3	Coating (paint finish)	Standard paint finish
Regreasing device	- / -	Color, paint shade	RAL7030
Grease nipple	-/-	Motor protection	(A) without
Condensate drainage holes	Yes	Method of cooling	IC411 - Self ventilated, surface cooled

Terminal box

Terminal box position	Top	Cable diameter from ... to ...	19.0 mm - 28.0 mm
Material of terminal box	Sheet Metal	Cable entry	2xM40x1.5
Type of terminal box	TB7 J03	Cable gland	2 Plugs
Contact screw thread	M5		
Max. cross-sectional area	25 mm ²		

Notes:

I_A/I_N = locked rotor current / current nominal
M_A/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

3) Efficiency value is valid only for sinusoidal line supply operation.

1) L_{10mh} according to DIN ISO 281 10/2010

Responsible department IN LVM	Technical reference	Created by SPC	Approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
SIEMENS	Document type Datasheet			Document status Released			
	MLFB and Order Code 1LE7501-1DC43-5AA4			Document number			
				Revision 01	Creation date 2024-09-27		
© INNOMOTICS 2024						Language en	Page 1/1