

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS

Motor type: 7CV3310C SIMOTICS SD - 315S - IM B3 - 6 p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	M	η <sup>3)</sup>			cosφ <sup>3)</sup>			I <sub>A</sub> /I <sub>N</sub>	M <sub>A</sub> /M <sub>N</sub>	M <sub>K</sub> /M <sub>N</sub>	IE-CL	
[V]±10%		[Hz]±5%	[kW]	[hp]	[A]	[1/min]	[kgf.m]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4					
Motordaten / Motor Data																			
415	Δ	50	75.00	-/-	134.00	991	74.0	723.0	95.1	95.3	95.0	0.82	0.76	0.66	7.1	3.1	3.1	IE3	
IM B3 / IM 1001			FS 315S		760 kg		SF:1		IS 12615 / IEC 60034-1			-							
Environmental conditions : -20 °C - +50 °C / 1,000 m										Locked rotor time (hot / cold) : 12 s   21 s									

Mechanical data

Sound pressure level 50Hz   60Hz	75 dB(A)	78 dB(A)	External earthing terminal	Yes (standard)
Moment of inertia   Rotor GD <sup>2</sup>	2.6060 kg m <sup>2</sup>   10.4239 kgf.m <sup>2</sup>		Vibration severity grade	A (Standard)
Bearing DE   NDE	6319 C3	6319 C3	Insulation	155(F) utilized to 130(B)
bearing lifetime			Duty type	S1
L <sub>10mh</sub> F <sub>Rad max</sub> according catalogue 50 60Hz <sup>1)</sup>	20,000 h	16,000 h	Direction of rotation	Bidirectional
L <sub>10mh</sub> F <sub>Rad min</sub> for coupling operation 50 60Hz <sup>1)</sup>	50,000 h	40,000 h	Frame material	Cast iron
Type of bearing	Locating (fixed) bearing, NDE		Forced ventilation motor details	- / -
Relubrication interval/quantity DE   NDE	40 g   40 g 6,000 h		Net weight of the motor (IM B3)	760 kg
Type of construction	IM B3 / IM 1001		Rotor weight	219 kg
Degree of protection	IP55		Data of anti condensation heating	-/- V, -/- W
Lubricants	Esso Unirex N3		Coating (paint finish)	Standard paint finish
Regreasing device	Yes (standard)		Color, paint shade	RAL7030
Grease nipple	M10x1 DIN 71412 A		Motor protection	(A) without
Condensate drainage holes	Yes		Method of cooling	IC411 - Self ventilated, surface cooled

Terminal box

Terminal box position	Top	Cable diameter from ... to ...	38.0 mm - 45.0 mm
Material of terminal box	Cast iron	Cable entry	2xM63x1.5
Type of terminal box	TB1 Q01	Cable gland	2 Plugs
Contact screw thread	M12		
Max. cross-sectional area	185 mm <sup>2</sup>		

<b>Notes:</b>			
I <sub>A</sub> /I <sub>N</sub> = locked rotor current / current nominal			
M <sub>K</sub> /M <sub>N</sub> = locked rotor torque / torque nominal			
M <sub>K</sub> /M <sub>N</sub> = break down torque / nominal torque			
3) Efficiency value is valid only for sinusoidal line supply operation.			
1) L <sub>10mh</sub> according to DIN ISO 281 10/2010			

Responsible department IN LVM	Technical reference	Created by SPC	Approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		<a href="#">Link documents</a> 	
	Document type Datasheet			Document status Released			
	MLFB and Order Code 1LE7503-3AC03-5AA4			Document number			
© INNOMOTICS 2024				Revision 01	Creation date 2024-09-27	Language en	Page 1/1