



♥ [ADD TO WISH LIST](#)

Share with your friends



Automation & Control

# A9-40-00 220-230V 50Hz / 230-240V 60Hz Contactor

Genuine Products

Dedicated Support

Doorstep Delivery

**₹6.60** + ₹119.99 (GST 18%)

**eMart**

- 1 +

[Buy Now](#)

[Add to Cart](#)

More Offers available from [10 sellers](#) starting at INR. 786.59

Pin Code

[Calculate Shipping](#)

Please enter your PIN Code to check the best offers

Product Id#: 1SBL141201R8000

[Be the first to review this product](#)

Sold and delivered by **System Controls and Switchgears**

A 9 4-pole contactors are mainly used for controlling non-inductive or slightly inductive loads (i.e. resistance furnaces...) and generally for controlling power circuits up to 690 V AC and 440 V DC. The contactors can also be used for many other applications such lighting... The A... series 4-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 4 N.O. main poles, front and side-mounted add-on auxiliary contact blocks - Control circuit: AC operated with laminated magnet circuit - Accessories: a wide range of accessories is available.

More about A9-40-00 220-230V 50Hz / 230-240V 60Hz Contactor

## Technical Specification

MRP (Indian Rupees)

Not for Retail Sale

Enquire Now



Number of Main Contacts NO	4
Compatibility	A Contactors
Max Mechanical Switching Frequency	3600 cycles per hour
Max Electrical Switching Frequency	AC-1 600 cycles per hour, AC-2 / AC-4 300 cycles per hour, AC-3 1200 cycles per hour
Conventional Free-air Thermal Current (Ith)	acc. to IEC 60947-4-1, Open Contactors q = 40 °C 26 ampere
Coil Consumption	Holding at Max. Rated Control Circuit Voltage 50 Hz 8 2 volt - ampere, Holding at Max. Rated Control Circuit Voltage 60 Hz 8 2 volt - ampere, Pull-in at Max. Rated Control Circuit Voltage 50 Hz 70 volt - ampere, Pull-in at Max. Rated Control Circuit Volta
Terminal Type	Screw Terminals
Rated Operational Voltage	Main Circuit 690 volt
Operate Time	Between Coil De-energization and NO Contact Opening 4 ... 11 millisecond, Between Coil Energization and NO Contact Closing 10 ... 26 millisecond
Rated Control Circuit Voltage (Uc)	50 Hz 220-230V; 60 Hz 230-240V
Rated Breaking Capacity AC-3 acc. to IEC 60947-4-1	8 x Ie AC-3
Rated Operational Power AC-3 (Pe)	(220 / 230 / 240 V) 2.2 KWT, (380 / 400 V) 2.5 KWT, (415 V) 4 KWT, (440 V) 4 KWT, (500 V) 5.5 KWT, (690 V) 5.5 KWT
Rated Operational Current AC-3 (Ie)	(220 / 230 / 240 V) 55 °C 9 ampere, (380 / 400 V) 55 °C 9 ampere, (415 V) 55 °C 9 ampere, (440 V) 55 °C 9 ampere, (500 V) 55 °C 9 ampere, (690 V) 55 °C 7 ampere
Rated Operational Current AC-1 (Ie)	(690 V) 40 °C 25 ampere, (690 V) 55 °C 22 ampere, (690 V) 70 °C 18 ampere
Rated Making Capacity AC-3 acc. to IEC 60947-4-1	10 x Ie AC-3
Rated Breaking Capacity acc. to IEC 60947-5-1	10 x Ie AC-15
Rated Frequency Limits	25 ... 400 hertz
Package Width	78 millimetre
Package Length	76 millimetre
Package Height	47 millimetre
Invoice Description	A9-40-00 220-230V 50Hz / 230-240V 60Hz Contactor
Product Range	A Contactors
Package Gross Weight	0.34 kilogram
Extended Product Type	A9-40-00 220-230V 50Hz / 230-240V 60Hz
Ambient Air Temperature	Close to Contactor for Storage -60 ... +80 degree Celsius, Near Contactor for Operation in Free Air (Uc) -40 ... +70 degree Celsius, Near Contactor for Operation in Free Air (0.85 ... 1.1 Uc) -40 ... +55 degree Celsius
Rated Insulation Voltage (Ui)	acc. to UL/CSA 600 volt, acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 volt
Product Class	Block Contactors

Enquire Now



Total GST Percentage	18.00
HSN Number	85364900
Country of origin	Bulgaria (BG) - Imported by ABB India Limited

[Download](#)

[Offers](#)

[Reviews](#)

Recently Viewed

 <p><u>A9-40-00 400-415V 50Hz / 415-440V 60Hz Contactor</u> 1SBL141201R8600 <b>Out of Stock</b></p>	 <p><u>A9-22-00 400-415V 50Hz / 415-440V 60Hz Contactor</u> 1SBL141501R8600 <b>Out of Stock</b></p>	 <p><u>A16-40-00 400-415V 50Hz / 415-440V 60Hz Contactor</u> 1SBL181201R8600 <b>Out of Stock</b></p>	 <p><u>A16-22-00 400-415V 50Hz / 415-440V 60Hz Contactor</u> 1SBL181501R8600 <b>Out of Stock</b></p>
--	--	--	---

☐ Write to Us

1800 420 0707

@ [contactabb.in@abb.com](mailto:contactabb.in@abb.com)

(Only for India Inquiries)

Disha - Plot No.5 & 6, 2nd Stage, Peenya Industrial Area IV, Peenya 560058, Bangalore, Karnataka, India.

Facebook

Twitter

LinkedIn

Youtube

COMPANY

Information

Payment Methods

About Us

Sell With Sellers

Our Returns Policy

BlogsExchange and Returns Policy

Privacy Policy

Terms of Use

How to create a Company Account

FAQ

Enquire Now

