

Genuine products

Dedicated  
Support

Doorstep Delivery

**eMart**[Home](#) > [Electrification](#) > [Automation & Control](#) > [Contactors](#) > [Contactors < 100A](#) > AL26-30-10 220V DC Contactor♥ **ADD TO WISH LIST**

Share with your friends



Automation &amp; Control

## AL26-30-10 220V DC Contactor

**₹2386.50** + ₹429.57 (GST 18%)

- 1 +

Buy Now

Add to Cart

Pin Code

Calculate Shipping

Please enter your PIN Code to check the best offers

Product Id#: 1SBL243001R8810

[Be the first to review this product](#)Sold and delivered by **PIGEON AGENCY**

AL26 contactors are mainly used for controlling 3-phase motors and generally for controlling power circuits up to 690 V AC or 220 V DC. The contactors can also be used for many other applications such as isolation, capacitor switching, lighting. The AL... series 1-stack 3-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 3 main poles, 1 built-in auxiliary contact, front and side-mounted add-on auxiliary contact blocks - Control circuit: DC operated with solid core magnet circuit. The polarity on the coil terminals (A1+ and A2-) must be respected - Accessories: a wide range of accessories is available. AL... contactors are fitted with low consumption DC coils and are suitable for a direct control by PLC outputs.

Enquire Now



More about AL26-30-10 220V DC Contactor

Technical Specification	
MRP (Indian Rupees)	Not for Retail Sale
Number of Main Contacts NO	3
Compatibility	AL Contactors
Max Mechanical Switching Frequency	3600 cycles per hour
Max Electrical Switching Frequency	(AC-1) 600 cycles per hour
Horsepower Rating UL/CSA	(200 ... 208 V AC) Three Phase 7-1/2 hp
Conventional Free-air Thermal Current (Ith)	acc. to IEC 60947-4-1, Open Contactors $\Theta$ = 40 °C 45 ampere
Coil Consumption	Average Holding Value, from Warm State 3.5 watt
Terminal Type	Screw Terminals
Operate Time	Between Coil De-energization and NO Contact Opening 12 ... 18 millisecond
Rated Operational Power AC-3 (Pe)	(415 V) 11 kilowatt
Rated Operational Current DC-13 (Ie)	(24 V) 6 / 144 ampere
Rated Operational Current AC-3 (Ie)	(415 V) 55 °C 26 ampere
Rated Operational Current AC-15 (Ie)	(500 V) 2 ampere
Rated Operational Current AC-1 (Ie)	(690 V) 40 °C 45 ampere
Rated Frequency Limits	25 ... 400 hertz
Rated Frequency (f)	Auxiliary Circuit 50 / 60 hertz
Number of Aux Contacts NO	1
Rated Short-time Withstand Current (Icw)	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 210 ampere
Package Width	100 millimetre
Package Length	134 millimetre
Package Height	62 millimetre
Invoice Description	AL26-30-10 220V DC Contactor
Product Range	AL Contactors
Package Gross Weight	0.75 kilogram
Extended Product Type	AL26-30-10 220V DC
General Use Rating UL/CSA	(600 V AC) 40 ampere

Enquire Now



Ambient Air Temperature	Close to Contactor Fitted with Thermal O/L Relay -25 ... 55 degree Celsius
Rated Insulation Voltage (Ui)	acc. to IEC 60947-4-1 1000 volt
Product Class	Block Contactors
Number Of Poles	3
Total GST Percentage	18.00
HSN Number	85364900

- Download
- Offers
- Reviews

Recently Viewed



AL26-30-10 110V DC Contactor  
1SBL243001R8610  
₹2,350.50



AL30-30-10 110V DC Contactor  
1SBL283001R8610  
₹4,734.04



KL70-123C Light Element  
1SFA616070R1238  
**Out of Stock**

Enquire Now





✉ Write to Us

1800 420 0707

@ [contactabb.in@abb.com](mailto:contactabb.in@abb.com)

(Only for India Inquiries)

Disha - Plot No.5 & 6, 2nd Stage, Peenya  
Industrial Area IV, Peenya 560058,  
Bangalore, Karnataka, India.



COMPANY

AboutSell Our Us With Sellers Us

INFORMATION

BlogsExchange and Returns Policy

Privacy Terms How to create a Policy of Use Company Account

PAYMENT METHODS

FAQ 