

PRODUCT-DETAILS

XT2N 160 Ekip LS/I In=63A 3p F F

XT2N 160 Ekip LS/I In=63A 3p F F



General Information	
Extended Product Type	XT2N 160 Ekip LS/I In=63A 3p F F
Product ID	1SDA067056R1
EAN	8015644007935
Catalog Description	XT2N 160 Ekip LS/I In=63A 3p F F
Long Description	C.BREAKER TMAX XT2N 160 FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC EKIP-LS/I R 63 A

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design	Design for Closing Resource Loops - Standard EN45555 - 58.1 %
Principles Recyclability Rate	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
End of Life Instructions	9AKK108468A2349
Group Waste to Landfill	UL 2799 Zero Waste To Landfill Validation available

Target	
Toxic Substances	9AKK108467A8326
Control Act - TSCA	

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1897
---	-----------------

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	e9538100-5f4d-4e14-bda3-68a38dd9536e Italy (IT)
Simplified SCIP	c7d18baf-942b-4b78-ae49-0632621e046f Finland (FI) 9f9d759e-4705-4d5f-9675-a000f506fc88 Netherlands (NL) 13d15eb4-e731-4159-8727-a5128baad645 Sweden (SE) e10e3cf9-e4cb-4ba5-b2ba-e32357969590 Germany (DE) 6a018556-1af2-46d1-be0c-e1920257b820 France (FR) a730426f-7169-4072-97fa-898d4ade89b5 Netherlands (NL) 93bc5631-9213-454c-8602-64103f0013dc Spain (ES) 5423d5c2-3a74-4aaa-837d-10a776114857 Netherlands (NL) 72b3d328-c844-4e73-8290-1130047bc3aa Germany (DE) 679b26f6-4b92-485b-a3f8-ec954757e96f Poland (PL) 6613a1a8-2685-4213-95a3-0d87b7595cb5 Netherlands (NL) 57d47c68-6390-4c3d-90d6-73149a4b8c8a Netherlands (NL) 7bf12ca9-f0d6-4ae1-8204-8deac95dee0a Estonia (EE) 5a3d8285-3916-4060-90e3-e978fd065932 Greece (GR) c6dadd79-1abd-40c9-8f7d-e8f509e1fc20 Portugal (PT) 88b820d2-e34f-4903-8686-07f47b98c13d Bulgaria (BG) e5134581-f3e7-4c5f-9d2d-2590838c9c7b Sweden (SE) 392b53c5-f7f2-40a4-8b81-8c1ec0131e0d Poland (PL) e8bfc112-6ca5-4bfc-8844-e3ee850cde9c Germany (DE) aea5accc-b97e-44a9-a065-5d73da887de7 Denmark (DK) 8310868e-f6a2-475c-a3ea-a95cdbf091e5 Germany (DE) 3a38b715-7954-4d07-958c-da2ea89a7c91 Croatia (HR) e09c8a16-7c50-4ddc-a6ae-ced76c5b253c Czech Republic (CZ) 8e7e51bc-aa53-4558-8b1f-553f05fcd2e1 Poland (PL) 95287f09-c2b1-4bd6-9a37-d30e0e0d50cf France (FR) 125cc667-bdaf-417f-9743-29d29f1e367f Norway (NO)

Ordering

Order Code US and Canada	XT2NE3063EFF000XXX
E-Number (Finland)	3602491
E-Number (Sweden)	3182025
EAN	8015644007935
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	90 mm
Product Net Height	130 mm
Product Net Depth /	82.5 mm

Length	
Product Net Weight	1.4 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	130 mm
Package Level 1 Height	208 mm
Package Level 1 Depth / Length	145 mm
Package Level 1 Gross Weight	1.698 kg
Package Level 1 EAN	8015644007935

Additional Information

Circuit Breaker Type to be Associated	Power Distribution
Connecting Capacity Main Circuit	Busbar 32.5..100 mm²
Current Type	AC
Electrical Durability	120 cycles per hour 8000 cycle
Mechanical Durability	240 cycles per hour 25000 cycle
Number of Poles	3
Opening Time	CB with SOR 15 ms CB with UVR 15 ms
Order Multiple	1 piece
Power Loss	at Rated Operating Conditions per Pole 1.7 W
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	Automatic Circuit Breaker
Rated Current (I _n)	63 A
Rated Frequency (f)	50 / 60 Hz
Rated Voltage (U _r)	690 V
Rated Impulse Withstand Voltage (U _{imp})	8 kV
Rated Insulation Voltage (U _i)	1000 V
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(220 V AC) 65 kA (230 V AC) 65 kA (240 V AC) 65 kA (380 V AC) 36 kA (415 V AC) 36 kA (440 V AC) 36 kA (500 V AC) 30 kA (525 V AC) 20 kA (690 V AC) 10 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu})	(220 V AC) 65 kA (230 V AC) 65 kA (240 V AC) 65 kA (380 V AC) 36 kA (415 V AC) 36 kA (440 V AC) 36 kA (500 V AC) 30 kA

	(525 V AC) 20 kA (690 V AC) 10 kA
Rated Uninterrupted Current (I _u)	160 A
Recommended Screw Driver	Main Circuit M6
Release	Ekip LS/I
Release Type	EL
Short-Circuit Performance Level	N
Standards	IEC
Sub-type	XT2
Terminal Connection Type	Front
Terminal Type	Bolt
Tightening Torque	6 N·m
Version	F
CAD Dimensional Drawing	1SDH002230A1001

Certificates and Declarations

ATEX Certificate	No certification needed
Data Sheet, Technical Information	1SDC210100D0206 1SDC210099D0206
Declaration of Conformity - CE	9AKK106713A5901
GL Certificate	1SDL000163R0093
LR Certificate	1SDL000163R0100
UL Certificate	No certification needed
VDE Certificate	No certification needed
Dimension Diagram	1SDH000721R0100
Mechanical Drawings	1SDH000721R0100
Wiring Diagram	1SDM000068R0001
Instructions and Manuals	1SDH000721R0001

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
UNSPSC	39120000
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

