



PRODUCT-DETAILS

FA1N/MS 1250 3p F F

FA1B 1000 3p F F



General Information

Extended Product Type	FA1N/MS 1250 3p F F
Product ID	1SDA085486R1
EAN	8015644923464
Catalog Description	FA1B 1000 3p F F
Long Description	BREAKING PART FORMULA AIR FA1B 1000 FIXED THREE-POLE WITH TERMINALS REAR HORIZONTAL FITTED WITH 4 AUXILIARY CONTACT OF C.BREAKER IN POSITION OPEN-CLOSED

Material Compliance

REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326

<b>Environmental</b>	
Environmental Information	9AKK108467A6707

<b>Ordering</b>	
EAN	8015644923464
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

<b>Dimensions</b>	
Product Net Width	214 mm
Product Net Height	291 mm
Product Net Depth / Length	184 mm
Product Net Weight	14 kg

<b>Container Information</b>	
Package Level 1 Units	box 1 piece
Package Level 1 Width	360 mm
Package Level 1 Height	360 mm
Package Level 1 Depth / Length	350 mm
Package Level 1 Gross Weight	16 kg
Package Level 1 EAN	8015644923464

<b>Additional Information</b>	
Product Main Type	Formula Air
Product Name	Switch-disconnector
Product Type	Air Circuit Breaker
Version	F

<b>Technical</b>	
Current Type	AC
Electrical Durability	30 cycles per hour
Mechanical Durability	60 cycles per hour
Neutral Pole Current ([ $I_n$ ])	100 %
Number of Poles	3
Rated Current ( $I_n$ )	1250 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	12 kV
Rated Insulation Voltage ( $U_i$ )	1000 V
Rated Operational Voltage	690 V AC
Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ )	for 1 s 50 kA for 3 s 30 kA
Rated Uninterrupted Current ( $I_u$ )	1250 A
Rated Voltage ( $U_r$ )	690 V
Short-Circuit Performance	N

Level	
Standards	IEC
Sub-type	FA1
Terminal Connection Type	Fixed Circuit-Breakers

Certificates and Declarations

Data Sheet, Technical Information	1SDC200044D0201
Declaration of Conformity - CE	9AAK10103A1376
Instructions and Manuals	1SDH001599R0002

Classifications

ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Formula AIR

