



PRODUCT-DETAILS

MP2-10B

MP2-10B Pushbutton



| General Information | |
|-----------------------|--|
| Extended Product Type | MP2-10B |
| Product ID | 1SFA611101R1006 |
| EAN | 7320500266694 |
| Catalog Description | MP2-10B Pushbutton |
| Long Description | <p>The MP2-10B Pushbutton is: Maintained - Flush - Black - Non-illuminated - Black Plastic - No contact block</p> <p>This Pushbutton is part of ABB's modular plastic range, the most versatile range with a high level of flexibility and market-leading electrical ratings. Engineered for total reliability, longer lifetime, and highest mechanical durability. Self-cleaning contacts ensure reliable operation without the need for maintenance, increasing uptime. A high degree of protection guarantees reliability in extreme environments. The innovative design simplifies the entire process, from selection to easy and quick, tool-free installation. The perfect solution for every application.</p> |

| Ordering | |
|------------------------|------------|
| Minimum Order Quantity | 10 piece |
| Customs Tariff Number | 8536501999 |

| Popular Downloads | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SFC151007C02__ |
| Instructions and Manuals | 1SFC151011M0201 |

| Dimensions | |
|----------------------------|----------|
| Product Net Width | 0.029 m |
| Product Net Height | 0.029 m |
| Product Net Depth / Length | 0.033 m |
| Product Net Weight | 0.012 kg |

| Technical | |
|-------------------------|--|
| Ambient Air Temperature | Operation -25 ... +70 °C Storage -40 ... +85 °C |
| Color | Black |
| Actuator Type | Flush |
| Bezel Material | Black Plastic |
| Illumination | Non-illuminated |
| Function | Maintained |
| Enclosure Type NEMA | Type1 Type12 Type13 Type3R Type4 Type4X |
| Mechanical Durability | 2 million |

| Environmental | |
|----------------------|------------|
| Degree of Protection | Front IP66 |

| Material Compliance | |
|---|--|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658 |
| REACH Declaration | 2CMT2022-006479 |
| RoHS Information | 2CMT2022-006498 |
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Toxic Substances Control Act - TSCA | 2CMT2023-006523 |
| WEEE Category | Product Not in WEEE Scope |

| Certificates and Declarations | |
|----------------------------------|-----------------|
| cULus Certificate | 9AKK107046A9925 |
| Declaration of Conformity - CE | 2CMT2015-005452 |
| Declaration of Conformity - UKCA | 2CMT2020-006121 |

| Container Information | |
|--------------------------------|---------------|
| Package Level 1 Units | bag 1 piece |
| Package Level 1 Width | 0.135 m |
| Package Level 1 Depth / Length | 0.145 m |
| Package Level 1 Height | 0.035 m |
| Package Level 1 Gross Weight | 0.015 kg |
| Package Level 1 EAN | 7320500266694 |

| Classifications | |
|------------------------------------|--|
| Object Classification Code | S |
| ETIM 6 | EC000221 - Front element for push button |
| ETIM 7 | EC000221 - Front element for push button |
| ETIM 8 | EC000221 - Front element for push button |
| eClass | V11.0 : 27371210 |
| UNSPSC | 39122216 |
| IDEA Granular Category Code (IGCC) | 5212 >> Push button for distribution board |
| E-Number (Finland) | 2313624 |
| E-Number (Norway) | 4372016 |
| E-Number (Sweden) | 3715016 |

| Categories |
|--|
| Low Voltage Products and Systems → Control Products → Pilot Devices → Modular Plastic Range → MP Pushbutton |
| Medium Voltage Products and Systems → Service → Spares and Consumables → Parts → All Spare Parts (Relays-SWG-CB) |

