



PRODUCT-DETAILS

# KSB-113R

## KSB-113R Signal Beacon



### General Information

|                       |  |
|-----------------------|--|
| Extended Product Type | KSB-113R   |
| Product ID            | 1SFA616080R1131                                      |
| EAN                   | 7320500202678  |
| Catalog Description   | KSB-113R Signal Beacon                               |
| Long Description      | KSB-113R Light Element Xenon tube Red Flashing light |

### Ordering

|                        |          |
|------------------------|----------|
| Minimum Order Quantity | 1 piece  |
| Customs Tariff Number  | 85369001 |
| Product Main Type      | KSB      |

### Popular Downloads

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SFC151007C02__ |
| Instructions and Manuals          | 1SFC151011M0201 |

|                            |         |
|----------------------------|---------|
| <b>Dimensions</b>          |         |
| Product Net Width          | 0.088 m |
| Product Net Depth / Length | 0.057 m |
| Product Net Height         | 0.07 m  |
| Product Net Weight         | 0.14 kg |

|  |   |
|--|---|
| <b>Technical</b>                               |   |
| Accessory Type                                 | Signal towers and beacons                                     |
| Color  | Red   |
| Enclosure Type NEMA                            | Type5   |
| Function                                       | Flashing light  |
| Lamp Type                                      | Xenon tube  |
| Rated Control Supply Voltage (U <sub>s</sub> ) | 115 V AC  |
| Rated Frequency (f)                            | 50 / 60 Hz  |
| Rated Operational Voltage                      | 115 V AC  |
| Standards                                      | CAN/CSA C22.2 No.14, IEC/EN 60947-1, IEC/EN 60947-5-1, UL 508 |

|  |   |
|--|---|
| <b>Environmental</b>                   |   |
| Ambient Air Temperature                | Operation -20 ... +50 °C<br>Storage -20 ... 50 °C |
| Degree of Protection                   | Front IP65  |
| Maximum Operating Altitude Permissible | Without Derating 2000 m                           |

|   |  |
|---|--|
| <b>Material Compliance</b>                  |  |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658  |
| REACH Declaration                           | 2CMT2022-006479  |
| RoHS Information                            | 2CMT2022-006498  |
| RoHS Status                                 | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Toxic Substances Control Act - TSCA         | 2CMT2023-006523  |
| WEEE B2C / B2B                              | Business To Business   |
| WEEE Category                               | 5. Small Equipment (No External Dimension More Than 50 cm)             |

|                                      |                 |
|--------------------------------------|-----------------|
| <b>Certificates and Declarations</b> |                 |
| Declaration of Conformity - CE       | 2CMT2015-005456 |

|                                |               |
|--------------------------------|---------------|
| <b>Container Information</b>   |               |
| Package Level 1 Units          | box 1 piece   |
| Package Level 1 Width          | 0.06 m        |
| Package Level 1 Depth / Length | 0.09 m        |
| Package Level 1 Height         | 0.075 m       |
| Package Level 1 Gross Weight   | 0.14 kg       |
| Package Level 1 EAN            | 7320500202678 |

Classifications

|                                    |                                  |
|------------------------------------|----------------------------------|
| eClass                             | V11.0 : 27143210                 |
| E-Number (Finland)                 | 2313591                          |
| ETIM 6                             | EC001042 - Signal tower complete |
| ETIM 7                             | EC001334 - Continuous luminaire  |
| ETIM 8                             | EC001334 - Continuous luminaire  |
| ETIM 9                             | EC001334 - Continuous luminaire  |
| IDEA Granular Category Code (IGCC) | 3937 >> Strobe or warning lights |
| Object Classification Code         | P                                |
| UNSPSC                             | 39111706                         |

Categories

Low Voltage Products and Systems → Control Products → Pilot Devices → Signal Towers and Beacons

