



PRODUCT-DETAILS

CE3T-10B-11

CE3T-10B-11 Machine Stop



360°

General Information	
Extended Product Type	CE3T-10B-11
Product ID	1SFA619500R1076
EAN	7320500260821
Catalog Description	CE3T-10B-11 Machine Stop
Long Description	<p>The CE3T-10B-11 Machine Stop is: Compact - Machine Stop - Twist release - Maintained - Mushroom 30mm - Black - Non-illuminated - 1NO+1NC - 1 NO - 1 NC - 24 ... 300 V</p> <p>This Machine Stop is part of ABB's compact range, the most efficient all-in-one solution available, reducing installation time and cost.</p> <p><u>The compact range has a high level of dust and water resistance.</u></p>

Ordering	
Minimum Order Quantity	10 piece
Customs Tariff Number	8536508090

Popular Downloads	
Data Sheet, Technical Information	1SFC151007C02__
Instructions and Manuals	1SFC151011M0201

Dimensions

Product Net Width	0.03 m
Product Net Height	0.03 m
Product Net Depth / Length	0.073 m
Product Net Weight	0.038 kg

Technical

Ambient Air Temperature	Operation -25 ... +70 °C Storage -40 ... +85 °C
Color	Black
Actuator Type	Mushroom 30mm
Bezel Material	n/a
Illumination	Non-illuminated
Function	Maintained
Sub-Function	Twist release
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	1
Enclosure Type NEMA	Type1 Type12 Type13 Type3R Type4 Type4X
Pollution Degree	3
Rated Insulation Voltage (U _i)	300 V
Rated Impulse Withstand Voltage (U _{imp})	6 kV
Rated Frequency (f)	50 / 60 Hz
Rated Operational Voltage	24 ... 300 V
Rated Operational Current DC-13 (I _θ)	(24 V) 0.3 A (125 V) 0.2 A
Rated Operational Current AC-15 (I _θ)	(240 V) 1 A
Power Loss	Maximum 5 W
Connecting Capacity	Flexible with Ferrule 1 x 0.5...1.5 mm² Flexible with Ferrule 2 x 0.5...1.5 mm² Flexible with Insulated Ferrule 1 x 0.5...1.5 mm² Flexible with Insulated Ferrule 2 x 0.5...1.5 mm² Flexible 1 x 0.5 ...1.5 mm² Flexible 2 x 0.5 ...1.5 mm² Solid 1 x 0.5...1.5 mm² Solid 2 x 0.5...1.5 mm²
Connection Type	Screw Clamp
Terminal Type	Screw Terminals
Tightening Torque	0.8 N·m
Wire Stripping Length	6 mm

Technical UL/CSA

Connecting Capacity	1x 22...14 AWG
UL/CSA	2x 22...14 AWG

Environmental

Degree of Protection

Front IP66
Front IP67
Front IP69K
Terminals IP20

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2022-006479
RoHS Information	2CMT2022-006498
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	52900c81-4bdc-4e96-b81e-b1b93e61a507 Sweden (SE)
Simplified SCIP	ab15a40f-123f-4724-a24b-b9e00927e1bd Germany (DE) d660b3e8-7e74-4552-9e07-c1f2639c32bd Poland (PL) f1118d3f-edbb-459c-b45e-2e6f7afd12a2 Hungary (HU) edd90d6c-4650-4324-b781-cdb3a6eb98c9 Greece (GR) 8aa4e284-83c3-4f34-a82d-2ed4747fbab Estonia (EE) 696fe0d0-9b7d-47e3-b47a-396985ea6d41 Netherlands (NL) 6e7758f7-4363-4841-85fb-cf18435ce921 Sweden (SE) 9cab0547-2ace-4cf2-978a-e8643d6479aa Poland (PL) 0a538e92-bc38-46a9-856b-0658576eb8d2 Portugal (PT) eefd03cc-cb5c-4f82-94ea-d4923b64cfad Bulgaria (BG) aaf86cf5-923e-484f-a9b2-c93b5353a70f France (FR) 031e5353-14c8-4a45-9a86-a4003d8a3944 Germany (DE) 59f746af-cf8e-4b91-80ba-c197e008129d France (FR) 551f397f-b999-41c5-9581-6a22bcd9bb5a9 Germany (DE) 256ed527-4013-42c2-a5cc-1d0d3de7a5bf Hungary (HU) c52011cb-a871-4392-abf7-7578ec3f7417 Spain (ES) 97ad3a0f-8ec1-47f4-84d2-7d893d7cd949 Belgium (BE) 4f0eef83-5270-47c9-b69d-7583a5dd92cb Finland (FI) 0212261c-900e-4400-bfc7-8e8fdcdcd999 Belgium (BE) 6d9896af-bfeb-4cda-928e-0c4eeaf73627 Italy (IT) b2169804-6cd9-409b-bbfe-748a9283d22c Germany (DE) c26c6a5a-0899-4577-8860-4a093d7434ef Norway (NO) 602357ed-48b7-4a49-8fde-eab12e5db119 Poland (PL) 2528f401-63bb-47bb-a29c-e4b5126d7b26 Czech Republic (CZ) 8f29f9bd-ef4f-42a2-9e04-c4930bab4078 Croatia (HR) 8658e042-7345-4e2a-873b-a9f596213e25 Germany (DE) a6c07477-700a-4957-80a5-8092014b1993 Denmark (DK)
Toxic Substances Control Act - TSCA	2CMT2023-006523
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

CB Certificate	CN54150
CQC Certificate	CQC2003010305054693
cULus Certificate	UL_E496500-20171020
cURus Certificate	UL_E496500-20171020
Declaration of Conformity - CCC	2020980305001187
Declaration of Conformity - CE	2CMT2019-005802
Declaration of Conformity - UKCA	2CMT2020-006121
DNV GL Certificate	9AKK107046A3749
EAC Certificate	EAC RU C-CN.ME77.B.00537/19

Container Information

Package Level 1 Units	bag 1 piece
Package Level 1 Width	0.165 m
Package Level 1 Depth /	0.09 m

Length	
Package Level 1 Height	0.035 m
Package Level 1 Gross Weight	0.04 kg
Package Level 1 EAN	7320500260821

Classifications

Object Classification Code	S
ETIM 6	EC002034 - Emergency stop complete
ETIM 7	EC001028 - Push button, complete
ETIM 8	EC001028 - Push button, complete
eClass	V11.0 : 27371228
UNSPSC	39122216
IDEA Granular Category Code (IGCC)	5212 >> Push button for distribution board
E-Number (Finland)	2312171
E-Number (Sweden)	3711550

Categories

Low Voltage Products and Systems → Control Products → Pilot Devices → Compact Range → CE Compact Emergency Stops and Machine Stops
Low Voltage Products and Systems → Control Products → Pilot Devices → Emergency Stop and Safety Stop

