



PRODUCT-DETAILS

CE3P-10B-11

CE3P-10B-11 Machine Stop



General Information	
Extended Product Type	CE3P-10B-11
Product ID	1SFA619501R1076
EAN	7320500355473
Catalog Description	CE3P-10B-11 Machine Stop
Long Description	The CE3P-10B-11 Machine Stop is: Compact - Machine Stop - Pull release - Maintained - Mushroom 30mm - Black - Non-illuminated - 1NO+1NC - 1 NO - 1 NC - 24 ... 300 V This Machine Stop is part of ABB's compact range, the most efficient all-in-one solution available, reducing installation time and cost. The compact range has a high level of dust and water resistance.

Ordering	
Minimum Order Quantity	10 piece
Customs Tariff Number	8536508090

Popular Downloads	
Data Sheet, Technical	1SFC151007C02_

Information	
Instructions and Manuals	1SFC151011M0201

Dimensions

Product Net Width	0.03 m
Product Net Height	0.03 m
Product Net Depth / Length	0.073 m
Product Net Weight	0.034 kg

Technical

Ambient Air Temperature	Operation -25 ... +70 °C Storage -40 ... +85 °C
Color	Black
Actuator Type	Mushroom 30mm
Bezel Material	n/a
Illumination	Non-illuminated
Function	Maintained
Sub-Function	Pull release
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	1
Enclosure Type NEMA	Type1 Type12 Type13 Type3R Type4 Type4X
Pollution Degree	3
Rated Insulation Voltage (U _i)	300 V
Rated Impulse Withstand Voltage (U _{imp})	6 kV
Rated Frequency (f)	50 / 60 Hz
Rated Operational Voltage	24 ... 300 V
Rated Operational Current DC-13 (I _e)	(24 V) 0.3 A (125 V) 0.2 A
Rated Operational Current AC-15 (I _e)	(240 V) 1 A
Power Loss	Maximum 5 W
Connecting Capacity	Flexible with Ferrule 1 x 0.5...1.5 mm ² Flexible with Ferrule 2 x 0.5...1.5 mm ² Flexible with Insulated Ferrule 1 x 0.5...1.5 mm ² Flexible with Insulated Ferrule 2 x 0.5...1.5 mm ² Flexible 1 x 0.5 ...1.5 mm ² Flexible 2 x 0.5 ...1.5 mm ² Solid 1 x 0.5...1.5 mm ² Solid 2 x 0.5...1.5 mm ²
Connection Type	Screw Clamp
Terminal Type	Screw Terminals
Tightening Torque	0.8 N·m
Wire Stripping Length	6 mm

Technical UL/CSA	
Connecting Capacity	1x 22...14 AWG
UL/CSA	2x 22...14 AWG

Environmental	
Degree of Protection	Front IP66 Front IP67 Front IP69K Terminals IP20

Material Compliance	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2022-006479
RoHS Information	2CMT2022-006498
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	b6de9685-77a1-4db6-97c6-5eee6a2126b6 Sweden (SE)
Simplified SCIP	039f09e1-7183-44b7-8f41-13f06518f1a4 Germany (DE) b9f3fdc4-8538-44c0-ad6c-cd48b2528eb7 Poland (PL) f2d4ba78-b1cb-4b28-9872-88e0a99717df Poland (PL) b996ebd0-4446-4675-b940-fc7c970e6cbe Estonia (EE) 51f49b10-4637-400d-8a57-47c8cefee032 Netherlands (NL) 5e0a6fea-370f-49a5-bff7-eb3740652ad4 Hungary (HU) 175d364e-6a97-4114-8b18-83314daa2f04 Belgium (BE) 4732ec56-78e2-4a12-9bce-545f05d152da France (FR) 3faa5154-5a6e-4f1c-809a-3af1e5f3394d Hungary (HU) 903e1f65-56d4-405b-a0b9-7f68055262c5 Spain (ES) c91a53b2-db52-4127-be88-b97267b49cc8 Greece (GR) 2c2dd300-968f-4ce4-88f5-cbb93b361fa0 Portugal (PT) 99f8d010-6fb4-49ab-b41a-2f9d02598c6a Czech Republic (CZ) 9f30d707-3ae5-4c5f-aafc-6afcc8a78193 Germany (DE) ab3a46f3-016d-45a3-a28c-c3b56fe4079f Croatia (HR) c591c495-b2f5-4b3b-9cd6-1597a4920402 Denmark (DK) 6f094a3b-156e-4ecf-8c29-c739a6beeb1d Germany (DE) 5ffd234e-e58b-43b6-a306-756ff85d2652 Poland (PL) 47fde792-ca14-403c-bd3b-a2d86deb5c34 Bulgaria (BG) c06fa98b-fef5-411a-aaf3-13f7dd86580c Sweden (SE) e50d6c45-a881-4489-b45a-247450828528 France (FR) 658fac61-dc04-4f14-9903-1e17c691e512 Germany (DE) 722a67c7-5e2a-4c51-b547-580f7428f24c Germany (DE) 0a9a5b1c-b025-40e0-b4bc-3da3fe768373 Belgium (BE) 12587b3e-7cdc-464e-b88b-c6ea3804e04a Italy (IT) 2d34dac5-92a6-4cf3-8a90-2a74f4aea5f4 Finland (FI) ab73026d-2e0b-45df-a7c4-4fa56c18d447 Norway (NO)
Toxic Substances Control Act - TSCA	2CMT2023-006523
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations	
CB Certificate	CN54150
CQC Certificate	CQC2003010305054693
cULus Certificate	UL_E496500-20171020
cURus Certificate	UL_E496500-20171020
Declaration of	2020980305001187

Conformity - CCC	
Declaration of Conformity - CE	2CMT2019-005802
Declaration of Conformity - UKCA	2CMT2020-006121
DNV GL Certificate	9AKK107046A3749
EAC Certificate	EAC RU C-CN.ME77.B.00537/19

Container Information

Package Level 1 Units	bag 1 piece
Package Level 1 Width	0.165 m
Package Level 1 Depth / Length	0.09 m
Package Level 1 Height	0.035 m
Package Level 1 Gross Weight	0.036 kg
Package Level 1 EAN	7320500355473

Classifications

Object Classification Code	S
ETIM 6	EC002034 - Emergency stop complete
ETIM 7	EC001028 - Push button, complete
ETIM 8	EC001028 - Push button, complete
eClass	V11.0 : 27371228
UNSPSC	39122216
IDEA Granular Category Code (IGCC)	5212 >> Push button for distribution board
E-Number (Finland)	2312172
E-Number (Sweden)	3711552

Categories

Low Voltage Products and Systems → Control Products → Pilot Devices → Compact Range → CE Compact Emergency Stops and Machine Stops

Low Voltage Products and Systems → Control Products → Pilot Devices → Emergency Stop and Safety Stop

