



PRODUCT-DETAILS

# CE4P-10B-11

## CE4P-10B-11 Machine Stop



General Information	
Extended Product Type	CE4P-10B-11
Product ID	1SFA619551R1076
EAN	7320500355480
Catalog Description	CE4P-10B-11 Machine Stop
Long Description	<p>The CE4P-10B-11 Machine Stop is: Compact - Machine Stop - Pull release - Maintained - Mushroom 40 mm - Black - Non-illuminated - 1NO+1NC - 1 NO - 1 NC - 24 ... 300 V</p> <p>This Machine Stop is part of ABB's compact range, the most efficient all-in-one solution available, reducing installation time and cost.</p> <p>The compact range has a high level of dust and water resistance.</p>

Ordering	
Minimum Order Quantity	10 piece
Customs Tariff Number	8536508090

Popular Downloads	
Data Sheet, Technical	1SFC151007C02__

Information

Instructions and Manuals	1SFC151011M0201
--------------------------	-----------------

# Dimensions

Product Net Width	0.04 m
Product Net Height	0.04 m
Product Net Depth / Length	0.073 m
Product Net Weight	0.038 kg

# Technical

Ambient Air Temperature	Operation -25 ... +70 °C Storage -40 ... +85 °C
Color	Black
Actuator Type	Mushroom 40 mm
Bezel Material	n/a
Illumination	Non-illuminated
Function	Maintained
Sub-Function	Pull release
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	1
Enclosure Type NEMA	Type1 Type12 Type13 Type3R Type4 Type4X
Pollution Degree	3
Rated Insulation Voltage (U <sub>i</sub> )	300 V
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	6 kV
Rated Frequency (f)	50 / 60 Hz
Rated Operational Voltage	24 ... 300 V
Rated Operational Current DC-13 (I <sub>e</sub> )	(24 V) 0.3 A (125 V) 0.2 A
Rated Operational Current AC-15 (I <sub>e</sub> )	(240 V) 1 A
Power Loss	Maximum 5 W
Connecting Capacity	Flexible with Ferrule 1 x 0.5...1.5 mm <sup>2</sup> Flexible with Ferrule 2 x 0.5...1.5 mm <sup>2</sup> Flexible with Insulated Ferrule 1 x 0.5...1.5 mm <sup>2</sup> Flexible with Insulated Ferrule 2 x 0.5...1.5 mm <sup>2</sup> Flexible 1 x 0.5 ...1.5 mm <sup>2</sup> Flexible 2 x 0.5 ...1.5 mm <sup>2</sup> Solid 1 x 0.5...1.5 mm <sup>2</sup> Solid 2 x 0.5...1.5 mm <sup>2</sup>
Connection Type	Screw Clamp
Terminal Type	Screw Terminals
Tightening Torque	0.8 N·m
Wire Stripping Length	6 mm

Technical UL/CSA	
Connecting Capacity	1x 22...14 AWG
UL/CSA	2x 22...14 AWG

Environmental	
Degree of Protection	Front IP66 Front IP67 Front IP69K Terminals IP20

Material Compliance	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2022-006479
RoHS Information	2CMT2022-006498
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	bad1b1ff-1e5e-46cf-8584-8a42568a2ff0 Sweden (SE)
Simplified SCIP	da7ce381-eb5d-45db-beae-24705af35e26 Germany (DE) b9ad929b-d756-409c-b4d6-d7f4e0dd4492 Portugal (PT) a207a0a4-4b68-45d2-a3f0-2d7d60eb57ba Bulgaria (BG) f4c490bf-3ac3-4a8c-b5ca-bab20a4a7901 Poland (PL) f4a7d4f4-74ad-4f42-b68f-5047a82ae800 Czech Republic (CZ) 60e4f9e1-b236-47f1-b546-ebbc58803c88 Netherlands (NL) dec2d586-5a4f-48e2-ad4a-b8ccaaecec04 Estonia (EE) 753a6789-ae99-49ca-af28-4aedd1a90c1d Hungary (HU) ba8e3f32-48cd-4ec6-88a6-764284c44435 Greece (GR) eeb47249-1a30-451a-b1a7-26308b247ad7 Spain (ES) 4fd03ae5-e52f-48e0-905d-5a861c0e3d73 France (FR) 3e9c7445-8861-4c62-9d88-37bdc079009b Hungary (HU) 5306b94f-7201-4d0e-963e-15852253a389 Germany (DE) 9db8488d-b1a4-4667-ad16-823182fcc05c Belgium (BE) b299ec29-266b-47d8-9bac-1b1f71939ac2 Germany (DE) 650c4659-6e20-450d-9429-4a773007f9d8 France (FR) 763d83da-d638-4625-863a-ca7127d61a27 Poland (PL) 6fda508e-db2e-4d4c-ad49-c4bce37d770d Sweden (SE) adc26b7f-d228-42cf-82a8-bf64dc78457d Norway (NO) 6f4ff3de-3483-45b2-a644-9af9caf10b37 Poland (PL) ea69f47a-f96d-410c-b225-75abd4dad186 Belgium (BE) 36dfdb11-f901-489e-adee-5121558f6e8a Italy (IT) 399e8f23-4105-43a3-a43b-63cdc683cdc5 Finland (FI) 250e39f5-5af8-4645-8ae0-9fe80d64967e Croatia (HR) adf63255-a738-4463-b0ef-6092b0155975 Germany (DE) 5ff3bcdd-905b-4a7a-ab33-010d2593e9fb Denmark (DK) 9263924d-1f97-4fd6-aed7-de417186f3e9 Germany (DE)
Toxic Substances Control Act - TSCA	2CMT2023-006523
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations	
CB Certificate	CN54150
CQC Certificate	CQC2003010305054693
cULus Certificate	UL_E496500-20171020
cURus Certificate	UL_E496500-20171020
Declaration of	2020980305001187

Conformity - CCC	
Declaration of Conformity - CE	2CMT2019-005802
Declaration of Conformity - UKCA	2CMT2020-006121
DNV GL Certificate	9AKK107046A3749
EAC Certificate	EAC RU C-CN.ME77.B.00537/19

Container Information

Package Level 1 Units	bag 1 piece
Package Level 1 Width	0.165 m
Package Level 1 Depth / Length	0.09 m
Package Level 1 Height	0.045 m
Package Level 1 Gross Weight	0.04 kg
Package Level 1 EAN	7320500355480

Classifications

Object Classification Code	S
ETIM 6	EC002034 - Emergency stop complete
ETIM 7	EC001028 - Push button, complete
ETIM 8	EC001028 - Push button, complete
eClass	V11.0 : 27371228
UNSPSC	39122216
IDEA Granular Category Code (IGCC)	5212 >> Push button for distribution board
E-Number (Finland)	2312175
E-Number (Sweden)	3711562

Categories

Low Voltage Products and Systems → Control Products → Pilot Devices → Compact Range → CE Compact Emergency Stops and Machine Stops

Low Voltage Products and Systems → Control Products → Pilot Devices → Emergency Stop and Safety Stop

