

PRODUCT-DETAILS

# AF140-40-00B-14

## AF140-40-00B-14 Contactor



General Information	
Extended Product Type	AF140-40-00B-14
Product ID	1SFL447102R1400
EAN	7320500505182
Catalog Description	AF140-40-00B-14 Contactor
Long Description	The AF140-40-00B-14 is a 4 pole - 690 V IEC or 600 V UL contactor with Main Circuit Bars, controlling motors up to 75 kW / 400 V AC (AC-3) / and switching power circuits up to 200 A (AC-1) or 175 A UL general use. Thanks to the AF technology, the contactor has a wide control voltage range (250-500 V 50/60 Hz and DC), managing large control voltage variations, reducing panel energy consumptions and ensuring distinct operations in unstable networks. Furthermore, surge protection is built-in, offering a compact solution. AF contactors have a block type design, can be easily extended with add-on auxiliary contact blocks and an additional wide range of accessories.

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads	
Data Sheet, Technical Information	1SBC100192C0206

Instructions and Manuals	1SFC100003M0201
CAD Dimensional Drawing	2CDC001079B0201
Dimension Diagram	1SFB535001G1121

Dimensions

Product Net Width	120 mm
Product Net Depth / Length	128 mm
Product Net Height	150 mm
Product Net Weight	1.95 kg

Technical

Number of Main Contacts NO	4
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	0
Number of Auxiliary Contacts NC	0
Rated Operational Voltage	Main Circuit 690 V
Rated Frequency (f)	Main Circuit 60 Hz
Conventional Free-air Thermal Current (I <sub>th</sub> )	acc. to IEC 60947-4-1, Open Contactors $\Theta$ = 40 °C 200 A
Rated Operational Current AC-1 (I <sub>e</sub> )	(690 V) 40 °C 200 A (690 V) 60 °C 175 A (690 V) 70 °C 160 A
Rated Operational Current AC-3 (I <sub>e</sub> )	(415 V) 55 °C 140 A (440 V) 55 °C 140 A (380 / 400 V) 55 °C 140 A (220 / 230 / 240 V) 55 °C 140 A
Rated Operational Power AC-3 (P <sub>e</sub> )	(415 V) 75 kW (440 V) 90 kW (380 / 400 V) 75 kW (220 / 230 / 240 V) 37 kW
Rated Breaking Capacity AC-3	8 x I <sub>e</sub> AC-3
Rated Making Capacity AC-3	10 x I <sub>e</sub> AC-3
Short-Circuit Protective Devices	gG Type Fuses 250 A
Rated Short-time Withstand Current Low Voltage (I <sub>cw</sub> )	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 1168 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 200 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 477 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 1460 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 674 A
Maximum Breaking Capacity	cos phi=0.45 (cos phi=0.35 for I <sub>e</sub> > 100 A) at 440 V 3000 A
Maximum Electrical Switching Frequency	(AC-1) 300 cycles per hour
Rated Insulation Voltage (U <sub>i</sub> )	acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	Main Circuit 8 kV
Mechanical Durability	5 million
Maximum Mechanical	300 cycles per hour

## Switching Frequency

Coil Operating Limits (acc. to IEC 60947-4-1) 0.85 x Uc Min. ... 1.1 x Uc Max. (at  $\theta \leq 70^\circ\text{C}$ )

Rated Control Circuit Voltage ( $U_c$ ) 50 Hz 250 ... 500 V  
 60 Hz 250 ... 500 V  
 DC Operation 250 ... 500 V

Coil Consumption Average Pull-in Value 50 Hz 260 V·A  
 Average Pull-in Value 60 Hz 260 V·A  
 Holding at Max. Rated Control Circuit Voltage 50 Hz 16.1 V·A  
 Holding at Max. Rated Control Circuit Voltage 60 Hz 16.1 V·A  
 Holding at Max. Rated Control Circuit Voltage DC 4 W  
 Pull-in at Max. Rated Control Circuit Voltage 50 Hz 205 V·A  
 Pull-in at Max. Rated Control Circuit Voltage 60 Hz 205 V·A  
 Pull-in at Max. Rated Control Circuit Voltage DC 230 W

Operate Time Between Coil De-energization and NO Contact Opening 40 ... 70 ms  
 Between Coil Energization and NO Contact Closing 20 ... 55 ms

Connecting Capacity Main Circuit Flexible 2 x 10 ... 70 mm<sup>2</sup>  
 Rigid Cu-Cable 1 x 10 ... 95 mm<sup>2</sup>

Connecting Capacity Auxiliary Circuit Flexible with Ferrule 2x 0.75 ... 2.5 mm<sup>2</sup>  
 Flexible with Insulated Ferrule 2x 0.75 ... 2.5 mm<sup>2</sup>  
 Flexible 2x0.75 ... 2.5 mm<sup>2</sup>  
 Solid 1 x 1 ... 4 mm<sup>2</sup>  
 Stranded 1 x 1 ... 4 mm<sup>2</sup>

Degree of Protection acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20  
 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP00

Terminal Type Main Circuit: Bars

## Technical UL/CSA

NEMA Size 4

Horsepower Rating NEMA (200 V AC) Three Phase 40 Hp  
 (230 V AC) Three Phase 50 Hp  
 (460 V AC) Three Phase 100 Hp  
 (575 V AC) Three Phase 100 Hp

Maximum Operating Voltage UL/CSA Main Circuit 600 V

General Use Rating UL/CSA (600 V AC) 200 A

Horsepower Rating UL/CSA (200 ... 208 V AC) Three Phase 15 Hp  
 (200 V AC) Three Phase 40 hp  
 (208 V AC) Three Phase 40 hp  
 (220 ... 240 V AC) Three Phase 20 Hp  
 (220 ... 240 V AC) Three Phase 50 hp  
 (440 ... 480 V AC) Three Phase 40 Hp  
 (440 ... 480 V AC) Three Phase 100 hp  
 (550 ... 600 V AC) Three Phase 50 Hp  
 (550 ... 600 V AC) Three Phase 125 hp

## Environmental

Ambient Air Temperature Close to Contactor Fitted with Thermal O/L Relay (0.85 ... 1.1 Uc) -25 ... 50 °C  
 Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 Uc) -40 ... 70 °C  
 Close to Contactor for Storage -40 ... 70 °C

Maximum Operating Altitude Permissible Without Derating 3000 m

## Material Compliance

Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658

REACH Declaration 2CMT2021-006202

RoHS Information 2CMT2021-006277

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	2CMT2023-006525
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

## Circular Value

ABB EcoSolutions	Yes
Circular Design Principles Recyclability Rate	Design for Closing Resource Loops - Standard EN45555 - 87.8 %
End of Life Instructions	1SFC100112M0001
Group Waste to Landfill Target	Non-hazardous waste is sent to a landfill, where there is no alternative option available within 100km of a facility
Improved Resource Efficiency for Customers	Product Efficiency - Product requires less energy to operate compared to similar product on market or older products from the same line
Sustainable Material Content	Recycled Metal - 37 %

## Eco Transparency

Environmental Product Declaration - EPD	1SFC100092D0201
--	-----------------

## Certificates and Declarations

ABS Certificate	14-LD1092198-PDA
BV Certificate	BV_36353_A0BV
CB Certificate	SEMKO_SE-70479M1
CQC Certificate	CQC2013010304604055
Declaration of Conformity - CCC	2020980304001304
Declaration of Conformity - CE	2CMT2015-005440
Declaration of Conformity - UKCA	2CMT2020-006118
DNV GL Certificate	DNV_E-14043
EAC Certificate	9AKK107046A8618
KC Certificate	9AKK107046A9911
LR Certificate	LR_14_70011(E1)
PRS Certificate	TE_2092_880423_16
RINA Certificate	ELE060313XG_002
RMRS Certificate	9AKK107045A6978
UL Certificate	E73397_20140710

## Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	147 mm
Package Level 1 Depth / Length	197 mm
Package Level 1 Height	155 mm

Package Level 1 Gross Weight	2.15 kg
Package Level 1 EAN	7320500505182

Classifications

Object Classification Code	Q
ETIM 4	EC000066 - Magnet contactor, AC-switching
ETIM 5	EC000066 - Magnet contactor, AC-switching
ETIM 6	EC000066 - Power contactor, AC switching
ETIM 7	EC000066 - Power contactor, AC switching
ETIM 8	EC000066 - Power contactor, AC switching
eClass	V11.0 : 27371003
UNSPSC	39121529
IDEA Granular Category Code (IGCC)	4758 >> Iec Contactors
E-Number (Finland)	3707176

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors → AF Contactors → AF140

