



PRODUCT-DETAILS

6819/51-24-500

Presence Detector Bluetooth 30 x 3 m 2300 W

studio white matt



General Information	
Extended Product Type	6819/51-24-500
Product ID	2CKA006800A2745
EAN	4011395217672
Catalog Description	Presence Detector Bluetooth 30 x 3 m 2300 W studio white matt
Long Description	<p>Master presence detector with mixed light measurement. For switching lighting systems that depend on brightness and movement. With Bluetooth interface for parameterization and operation. Adjustment of all setting options via smartphone or tablet. Light control via smartphone or tablet app. With power relays for LED operation. Detection range (for installation height of 3 m): rectangular Walking persons: crosswise to the detector 30 m x 3 m, frontal 20 m x 3 m. Extension of the detection range by means of master/slave combination. Mounting height 27 mm. For semi-automatic, comfort and fully automatic operation. Additional activation/deactivation possibility through pushbutton input. With continuous light/continuous off function (8 hours), activation via intelligent extension unit input possible. With selectable presence simulation in case of non-presence. With integrated storage of ON period (energy monitor). With brightness-independent test mode for evaluating the detection zone. With detection display in test mode. Ceiling installation using integrated spring bracket. Twist protection via additional quick tensioning. Adjustment elements accessible on the front side. Surveillance density: 92 sectors with 368 switching segments Individual deactivation and adjustment of sensitivity of individual sensors possible. Switch-off delay: approx. 1 min. - 30 min. or short-time pulse adjustable. With selectable dynamic switch-off delay. Suitable for false ceilings with a board thickness from 9 to 25 mm.</p>

Installation

Mounting Type	Built-in
Mounting Position	Ceiling
Mounting Height	Optimum 2 ... 4 m

Environmental

Ambient Air Temperature	Operation -5 ... +45 °C
Degree of Protection	IP40

Technical

Data Sheet, Technical Information	2CKA001673B9577
Function	Setting Options by Bluetooth
Measuring Range	30 x 3 m
Number of Outputs	1
Number of Switching Zones	368
Transmission Standard	Bluetooth
Minimum Switching Time	Switch-On 60 second [unit of time]
Connection Type	Plug Clamp
Sensor Type	Passive infrared
Illuminance	5 ... 2000 lx
Sensor Detection Range	360 ° Horizontal 90 ... 360 °

Electrical

Rated Voltage (U _r)	230 V AC
Auxiliary Voltage AC/DC	110 V AC/DC 230 V AC/DC
Input Voltage Type	AC
Current Range	Maximum 800 A
Rated Frequency (f)	50 / 60 Hz
Maximum Switching Power	2300 W
Load Type	230 V incandescent lamps
Power Loss	0.3 W

Design

Surface Finishing	Untreated Matt
Material	Thermoplastic
RAL Number	Similar to RAL 9016
Color	studio white matt

Dimensions

Product Net Width	94 mm
Product Net Height	94 mm
Product Net Depth / Length	76 mm
Product Net Weight	170.4 g
Built-In Depth (t ₂)	49 mm

Ordering

E-Number (Sweden)	1301141
-------------------	---------

Material Compliance

RoHS Information	2CKA200000E6492
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
REACH Declaration	2CKA309999E9999
REACH Information	True - contains substances > 0.1 mass percentage
REACH Date	20240705
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Certificates and Declarations

Declaration of Conformity - CE	2CKA200000E6492
--------------------------------	-----------------

Classifications

ETIM 9	EC000133 - Movement sensor/presence detector complete
eClass	V11.0 : 27144007
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer

Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CKA006800A2801	Presence Detector studio white matt	6889/50-24-500	1	piece
2CKA006499A0002	Extension Module	6494-500	1	piece
2CKA006899A2304	Protection Cover alpine white	6898	1	piece

Categories

Low Voltage Products and Systems → Wiring Accessories - StandAlone Electronics → Presence Detector → Professional Series

