Product datasheet

Specifications



motor-mechanism - MCH - 200..250 V DC

33188

Range of product	MasterPact NT
Range	MasterPacT
Device short name	gear motor MCH
Product or component type	Motor mechanism
Device application	Automatic spring charging
Range compatibility	Masterpact (MasterPact NT) circuit breaker
[Uc] control circuit voltage	200/250 V DC

Complementary

Control type	Motor mechanism
Maximum charging time	3 s
Maximum operating frequency	<= 3 cycles per minute
Threshold tripping voltage	0.851.1 Un
Maximum power consumption in VA	180 W
Accessory / separate part	Spare parts for MasterPact NT

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.500 cm
Package 1 Width	12.500 cm
Package 1 Length	17.500 cm
Package 1 Weight	783.500 g
Unit Type of Package 2	S03
Number of Units in Package 2	16
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm

12.949 kg
P12
128
45.000 cm
80.000 cm
120.000 cm
115.592 kg

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes

Contractual warranty

Warranty 18 months

Recommended replacement(s)