



Figure similar

accessory for VL630; VL800 motorized operating mechanism 220-250V AC/DC for MCCB greater than, equal to \*E02\*01\*

Model	
product brand name	SETRON
product designation	Motorized operating mechanism
design of the product	Accessories for VL630; VL800
type of the driving mechanism	motorized operating mechanism
General technical data	
operating frequency maximum	120 1/h
Voltage	
fuse protection type for external auxiliary power supply required	NEOZED fuse (gL/gG): 2 A / miniature circuit breaker, C char.: 2 A
<b>operating range factor control supply voltage rated value</b>	
• at DC initial value	0.85
• at DC full-scale value	1.1
• at AC at 50 Hz initial value	0.85
• at AC at 50 Hz full-scale value	1.1
• at AC at 60 Hz initial value	0.85
• at AC at 60 Hz full-scale value	1.1
Protection class	
protection class IP	IP30
Control current	
operating apparent power	100 VA
control supply voltage	
• at DC rated value minimum	250 V
• at DC rated value maximum	220 V
• at AC at 50 Hz rated value minimum	220 V
• at AC at 50 Hz rated value maximum	250 V
• at AC at 60 Hz rated value minimum	220 V
• at AC at 60 Hz rated value maximum	250 V
pulse duration minimum	50 ms
Connections	
stripped length	9 mm
connectable conductor cross-section solid	
• minimum	1.5 mm <sup>2</sup>
• maximum	1.5 mm <sup>2</sup>
connectable conductor cross-section stranded	
• minimum	1.5 mm <sup>2</sup>
• maximum	1.5 mm <sup>2</sup>
connectable conductor cross-section finely stranded with core end processing	
• minimum	1.5 mm <sup>2</sup>

- maximum

1.5 mm²

#### Mechanical Design

height	168.9 mm
width	190 mm
depth	182.1 mm
net weight	2 329 g

#### Environmental conditions

ambient temperature during operation	
• minimum	-25 °C
• maximum	70 °C
ambient temperature during storage	
• minimum	-40 °C
• maximum	80 °C

#### Certificates

reference code according to IEC 81346-2	M
---	---

#### Approvals Certificates

General Product Approval	Test Certificates	Marine / Shipping
--------------------------	-------------------	-------------------



[Confirmation](#)



[Special Test Certificate](#)



Marine / Shipping	other
-------------------	-------



[Confirmation](#)

other	Environment
-------	-------------

[Miscellaneous](#)

[Environmental Confirmations](#)

[Environmental Confirmations](#)

#### Further information

##### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL9600-3ME10>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VL9600-3ME10>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VL9600-3ME10](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL9600-3ME10)

##### CAX-Online-Generator

<http://www.siemens.com/cax>

##### Tender specifications

<http://www.siemens.com/specifications>

last modified:

3/12/2024

