

Product datasheet

Specifications



motor mechanism MCH 24 to 30 V DC

47888

Main

Range of product	MasterPact NW
Range	MasterPacT
Device short name	gear motor MCH
Product or component type	Motor mechanism
Device application	Automatic spring charging
Range compatibility	Masterpact MasterPact NW circuit breaker EasyPact EasyPact MVS circuit breaker
[Uc] control circuit voltage	24/32 V DC

Complementary

Control type	Motor mechanism
Maximum charging time	4 s
Maximum operating frequency	<= 3 cycles per minute
Threshold tripping voltage	0.85...1.1 Un
Maximum power consumption in VA	180 W
Accessory / separate part category	Spare parts for MasterPact NW

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.8 cm
Package 1 Width	13.4 cm
Package 1 Length	23.0 cm
Package 1 Weight	1.888 kg
Unit Type of Package 2	S03
Number of Units in Package 2	6
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm

Package 2 Weight	11.815 kg
------------------	-----------

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)