

# Product datasheet

Specifications



external power supply module, input voltage 380 V AC to 415 V AC 50/60 Hz, output voltage 24 V DC, output current 1 A

54445

⚠ Discontinued

⚠ Discontinued on: 02 March 2020

## Main

Product or component type	External power supply module
Device application	Power supply
Range compatibility	Masterpact MasterPact MTZ Masterpact MasterPact NT Masterpact MasterPact NW ComPact ComPact NSX ComPact ComPact NSX DC PowerPact PowerPact Multistandard
Accessory / separate part type	Control units accessories Trip unit accessories

## Complementary

Trip unit name	MicroLogic
Power supply type	Regulated switch mode
[Us] rated supply voltage	380...415 V AC 50/60 Hz tolerance: +10 % -15 %
Input voltage limits	323...456.5 V AC at 47.5...63 Hz
Output voltage	24 V DC +/-5 %
Overvoltage category	IV conforming to IEC 62477-1
Height	88 mm
Width	105 mm
Depth	59 mm

## Environment

Compatibility code	CB_EXTERNAL_POWERSUPPLY
--------------------	-------------------------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.7 cm
Package 1 Width	10 cm
Package 1 Length	12 cm
Package 1 Weight	359 g

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes

Recommended replacement(s)