



Undervoltage release 230 V AC, with 6 terminals for miniature circuit breaker 5SL4, 5SY, 5SP RCBO 5SU1, FI 5SV (for 5SU1 handle coupler 5ST3805-1 is required)

| Model  |                      |
|--|----------------------|
| product brand name                                     | SENTRON              |
| product designation                                    | Undervoltage release |
| General technical data                                 |                      |
| switching function ON-delay/instantaneous contact      | No                   |
| type of voltage of the operating voltage for actuation | AC                   |
| Control current  |                      |
| control supply voltage                                 |                      |
| • at AC at 50 Hz rated value minimum                   | 230 V                |
| • at AC at 50 Hz rated value maximum                   | 230 V                |
| • at AC at 60 Hz rated value minimum                   | 230 V                |
| • at AC at 60 Hz rated value maximum                   | 230 V                |
| Suitability  |                      |
| suitability for integration                            |                      |
| • motor starter protector                              | No                   |
| • overload relay                                       | No                   |
| suitability for use                                    |                      |
| • load switch  | No                   |
| • circuit breaker                                      | No                   |
| number of NC contacts                                  | 0                    |
| number of NO contacts                                  | 2                    |
| number of CO contacts                                  | 0                    |
| Connections  |                      |
| type of electrical connection                          | screw terminal       |
| Mechanical Design                                      |                      |
| height   | 90 mm                |
| depth  | 70 mm                |
| net weight   | 114 g                |
| Approvals Certificates                                 |                      |
| General Product Approval                               | other                |



[Confirmation](#)

[Miscellaneous](#)



[Miscellaneous](#)

|                              |  |  |
|------------------------------|--|--|
| other                        | Railway                                  | Environment                                |
| <a href="#">Confirmation</a> | <a href="#">Special Test Certificate</a> | <a href="#">Confirmation</a>               |
|                              |  | <a href="#">Environmental Confirmation</a> |

**Further information****Information on the packaging**

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3040>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3040>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5ST3040](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3040)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>





