

Product datasheet

Specifications



ET6G PROTECTION RELAY FOR MVS

65479

Main

Range of product	EasyPact MVS
Product or component type	Control unit
Circuit breaker application	Industrial Standard
Poles description	4P 3P
Protected poles description	3D + N/2 4D 3D
Neutral position	Left
Network type	AC
Trip unit name	ET6G
Trip unit technology	Micro-processor based
Trip unit rating	800...4000 A

Complementary

Network frequency	50/60 Hz
Mounting mode	Fixed Drawout
[Ue] rated operational voltage	690 V AC 50/60 Hz conforming to IEC 60947-2
Neutral protection setting	Without protection (3D) 0.5 x Ir (3D + N/2) 1 x Ir (4D)
Trip unit protection functions	LSIG
Protection type	Overload protection (long time) Short time short-circuit protection Earth fault Instantaneous short-circuit protection
Fault indication	Short-circuit Overload Earth fault Internal fault
Long time pick-up adjustment type Ir	Adjustable 9 settings
Long time pick-up adjustment range	0.4...1 x In
Long time delay adjustment type	Adjustable 9 settings

[Tr] long-time delay adjustment range	0.5...24 s (6 x Ir), accuracy: 0...- 20 %
Thermal memory	20 minutes before and after tripping
Short-time pick-up adjustment type Isd	Adjustable 9 settings
[Isd] short-time pick-up adjustment range	1.5...10 x Ir
Short-time delay adjustment type	Adjustable 5 settings
[Tsd] short-time delay adjustment range	100...400 ms
Instantaneous pick-up adjustment type Ii	Adjustable 9 settings
Instantaneous pick-up adjustment range	2...15 x In, accuracy: +/- 10 % Off
Ground-fault time delay adjustment type -tg	Adjustable 5 settings
Ground-fault pick-up adjustment type	Adjustable 9 settings
[Tg] ground-fault time delay adjustment range	100...400 ms
[Ig] ground-fault pick-up adjustment range	0.2...1 x In (400 A < In =< 1000 A), accuracy: +/- 10 % 500...1200 x In (In >= 1250 A), accuracy: +/- 10 %
Zone selective interlocking ZSI	With
Height	200 mm
Width	55 mm
Depth	75 mm
Net weight	0.213 kg

Environment

Ambient air temperature for operation	-5...70 °C
Ambient air temperature for storage	-25...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.0 cm
Package 1 Width	8.0 cm
Package 1 Length	21.5 cm
Package 1 Weight	235.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	15
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	3.936 kg
Package 3 Height	30 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)