

# Product datasheet

Specifications



## PratiKa industrial socket - 63 A - 3P + N + E - 380...415 V AC - IP67

81183

### Main

|                           |               |
|---------------------------|---------------|
| Range                     | Mureva        |
| Product or component type | Socket        |
| Device short name         | Mureva socket |
| Plug, socket category     | Low voltage   |
| Poles description         | 3P + N + E    |
| Network type              | AC            |
| Outlet standard           | Industrial    |

### Complementary

|                                     |   |
|-------------------------------------|---|
| Mounting mode                       | Wall-mounted  |
| Plug, socket, control station shape | Angled  |
| [In] rated current                  | 63 A  |
| [Ue] rated operational voltage      | 380...415 V   |
| Network frequency                   | 50/60 Hz  |
| Ground lug clockwise position       | 6 h   |
| Plug, socket material               | Housing: self-extinguishing engineering polymer                                   |
| Contacts material                   | Pins: stainless steel<br>Sleeves: nickel plated brass<br>Springs: stainless steel |
| Connections - terminals             | Captive screws, completely loosened   |
| Cable cross section                 | 6...25 mm²  |
| Cable entry                         | Cable gland   |
| Thread type                         | Pg 36   |
| Net weight                          | 1.02 kg   |
| Base dimension                      | 104 x 162 mm  |
| Height                              | 255 mm  |
| Width                               | 104 mm  |
| Depth                               | 180 mm  |
| Colour                              | Grey (RAL 7035)   |

|                |     |
|----------------|-----|
| Voltage colour | Red |
|----------------|-----|

## Environment

|                                       |   |
|---------------------------------------|---|
| Standards                             | EN 60309-2<br>EN 60309-1                        |
| IP degree of protection               | IP67 conforming to IEC 60529                    |
| IK degree of protection               | IK08 conforming to EN 62262                     |
| Fire resistance                       | 850 °C conforming to IEC 60695-2-11             |
| Relative humidity                     | 50 % at 40 °C<br>70 % at 30 °C<br>90 % at 20 °C |
| Ambient air temperature for operation | 35 °C ( 86400 s )                               |

## Packing Units

|                              |            |
|------------------------------|------------|
| Unit Type of Package 1       | PCE        |
| Number of Units in Package 1 | 1          |
| Package 1 Height             | 10.800 cm  |
| Package 1 Width              | 18.000 cm  |
| Package 1 Length             | 25.500 cm  |
| Package 1 Weight             | 1.050 kg   |
| Unit Type of Package 2       | S03        |
| Number of Units in Package 2 | 5          |
| Package 2 Height             | 30.000 cm  |
| Package 2 Width              | 30.000 cm  |
| Package 2 Length             | 40.000 cm  |
| Package 2 Weight             | 5.649 kg   |
| Unit Type of Package 3       | P12        |
| Number of Units in Package 3 | 40         |
| Package 3 Height             | 45.000 cm  |
| Package 3 Width              | 80.000 cm  |
| Package 3 Length             | 120.000 cm |
| Package 3 Weight             | 57.192 kg  |

## Offer Sustainability

|                       |   |
|-----------------------|---|
| REACH Regulation      | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive     | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a>                     |
| China RoHS Regulation | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information |
| Circularity Profile   | No need of specific recycling operations  |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

## Recommended replacement(s)