

9013FHG12J52X

Pumptrol, air compressor switch 9013FH, fixed differential, Off at 125 PSI, low hp

Main

| | |
|------------------------------|---|
| Range of Product | Pumptrol |
| Pressure sensor name | 9013FH |
| Pressure sensor size | 150 psi (1034.21 kPa) |
| Value of setting | Off at 125 psi |
| Electrical circuit type | Power circuit |
| Product Specific Application | Control small electrically driven air compressors |
| Quantity per Set | 1 |
| Type of Packing | Individual |

Complementary

| | |
|-------------------------------------|--|
| Pressure sensor type | Electromechanical pressure switch |
| Controlled fluid | Air 32...158 °F (-0...70 °C)) |
| Adjustable range on rising pressure | 70...150 psi (482.6...1034.2 kPa) |
| Approximate fixed differential | 30 psi (206.8 kPa) |
| Destruction pressure | 220 psi (1516.8 kPa) |
| Pressure actuator | Diaphragm |
| Pressure switch type of operation | Regulation between 2 thresholds |
| Scale type | Fixed differential |
| Setting | Internal |
| Local display | Without |
| Contacts type and composition | 2 NC, snap action, DPST-DB, Form YY |
| Cable entry number | 2 0.88 in (22.35 mm) cable entries with 0.84 in across flats UL 508 |
| Electrical connection | Screw-clamp terminals 10 AWG Screw-clamp terminals 5.261 mm² |
| Fluid connection type | 0.25 inch NPSF internal UL 508 |
| Short-circuit protection | 20 A cartridge fuse gG |
| Materials in contact with fluid | Zinc plated steel or equivalent flange Nitrile (Buna-N) or equivalent rubber diaphragm |
| Material | Polypropylene: Cover Noryl thermoplastic resin or equivalent: Cover |
| Operating position | Any position |
| Motor power kW | 1.1 KW 1.5 hp)115 V AC, 1 phase 1.5 KW 2 hp)230 V AC, 1 phase 1.5 KW 2 hp)115 V AC, 3 phase 2.2 KW 3 hp)230 V AC, 3 phase 0.75 KW 1 hp)460 V AC, 3 phase 0.75 kW 1 hp)575 V AC, 3 phase |
| Electrical durability | 100000 cycles 10 cyc/mn |
| Mechanical durability | 300000 cycles |
| Terminal block type | 4 terminals |
| Maximum operating rate | 10 cyc/mn |
| [Ui] rated insulation voltage | 575 V UL 508 |
| Net Weight | 1 lb(US) (0.5 kg) |
| Repeat accuracy | +/- 3 % |
| Terminals description ISO n°1 | L1-T1 L2-T2 |
| Width | 2.78 in (70.61 mm) |

| | |
|----------------------|------------------------------|
| Height | 3.71 in (94.23 mm) |
| Depth | 3.76 in (95.50 mm) |
| Factory modification | 2-way pressure release valve |

Environment

| | |
|---------------------------------------|--------------------------------------|
| Standards | UL 508 CE |
| Ambient Air Temperature for Operation | -30.0000002...70.0 °C (-22...158 °F) |
| Ambient Air Temperature for Storage | -30.0000002...70.0 °C (-22...158 °F) |
| Protective treatment | None |
| NEMA degree of protection | NEMA 1 UL 50 |
| IP degree of protection | IP20 conforming to IEC 60529 |
| Product Certifications | CSA[RETURN]UL Listed |

Ordering and shipping details

| | |
|-------------------|--------------|
| Category | US1CP7I21533 |
| Discount Schedule | CP7I |
| GTIN | 785901522935 |
| Returnability | Yes |
| Country of origin | MX |

Packing Units

| | |
|------------------------------|------------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 10.160 in (25.806 cm) |
| Package 1 Width | 4.0000000000 in (10.16 cm) |
| Package 1 Length | 25.806 in (65.548 cm) |
| Package 1 Weight | 13.920 oz (394.625 g) |
| Unit Type of Package 2 | CAR |
| Number of Units in Package 2 | 20 |
| Package 2 Height | 8.800 in (22.352 cm) |
| Package 2 Width | 8.300 in (21.082 cm) |
| Package 2 Length | 14.800 in (37.592 cm) |
| Package 2 Weight | 18.63 lb(US) (8.45 kg) |
| Unit Type of Package 3 | PAL |
| Number of Units in Package 3 | 560 |
| Package 3 Height | 40.0000000000 in (101.6 cm) |
| Package 3 Width | 40.0000000000 in (101.6 cm) |
| Package 3 Length | 48.0000000000 in (121.92 cm) |
| Package 3 Weight | 522.00 lb(US) (236.775 kg) |

Offer Sustainability

| | |
|--|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| For all Reach Rohs enquiries contact us at | sustainability@tesensors.com |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|