## **Product datasheet**

Specifications



## VTPN Distribution board, Acti9, 4 ways, 160A MCCB, double door metal, IP43

A9HVN04M

via	un
-----	----

Range	Acti9
Product name	VTPN
Product or component type	Consumer unit
Device application	Distribution
Colour	White (RAL 9003)
Provided equipment	Removable gland plates Removable centre plates Earthing bar Neutral bar Fishbone busbar Busbar link Cable shroud
Door type	Plain

Complementary		
Enclosure mounting	Flush Surface	
Protection device type	Main incomer: molded case circuit breaker (MCCB) - 3P or 4P - 160 A Outgoer: miniature circuit breaker (MCB) - 1P or 3P - 63 A	
[lcw] rated short-time withstand current	25 kA for 0.5 s	
[In] rated current	160 A	
[Ui] rated insulation voltage	500 V	
[Uimp] rated impulse withstand voltage	4 kV	
Total number of 18 mm modules	12	
Number of ways	4 ways	
Enclosure/Cubicle description	Double door enclosure	
Enclosure material	Galvanized steel box Galvanized steel cable gland plate Galvanized steel mounting plate CRCA door CRCA central plate	
Door opening side	Reversible	
Height	558 mm external:	
Width	416 mm external:	-

Depth

155 mm external:

Net weight	14.6 kg
Environment	
IP degree of protection	IP43
IK degree of protection	IK09
Standards	IS 8623-1 IS 8623-3 IEC 61439-3
Product certifications	NABL
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.5 cm
Package 1 Width	55.8 cm
Package 1 Length	41.6 cm
Package 1 Weight	15.6 kg
Offer Sustainability	
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information

## Recommended replacement(s)

Yes

RoHS exemption information