Product datasheet

Specification





voltage transformer - 230..400 V - 2 x 115 V - 1 KVA

Local distributor code: 389707082

ABT7PDU100G

- ! To be discontinued on: 30 May 2024
- ! To be end-of-service on: 30 May 2025

! To be discontinued

EAN Code: 3389119401265

Main

Range Of Product	Modicon Transformer Universal		
Product Or Component Type Safety and isolation transformer			
Rated Power In Va	1000 VA		
Input Voltage	230 V AC single phase, terminal(s): N-L1 400 V AC phase to phase, terminal(s): L1-L2		
Output Voltage	115/230 V AC		
Secondary Winding	Double		
Protective Cover	Without		
Ambient Air Temperature For Operation	-2060 °C		

Complementary

Input Voltage Limits	207 252 1/
input voitage Limits	207253 V
	360440 V
Network Frequency Limits	4763 Hz
Input Voltage Tolerance	+/- 15 V
Efficiency	92 %
Power Dissipation In W	87 W
Voltage Variation At Nominal Load	0.0315 at 230 V
3	0,034 at 400 V
Output Sustained Overvoltage	0,035 (no load, hot state)
Maximum Voltage Drop At Rated Load	4.08 %
No Load Losses	31.09 W
Short-Circuit Voltage	0,038
Output Protection Type	Against overload, protection technology: with additional protection fuses or circuit-
	breakers in Selection of Protection
	Against overvoltage, protection technology: with additional protection fuses or circuit-
	breakers in Selection of Protection
	Against short-circuits, protection technology: with additional protection fuses or circuit-breakers in Selection of Protection
Connections - Terminals	For input connection: screw type terminals, connection capacity: 5 x 4 mm² AWG 11
	For input ground connection: screw type terminals, connection capacity: 1 x 4 mm ² AWG 11
	For output connection: screw type terminals, connection capacity: 6 x 10 mm² AWG 6
Marking	CE

17 Apr 2024 Life Is On Schneider

Fixing Mode	y 4 screws diameter: 7 mm on vertical panel, operating position: horizontal y 4 screws diameter: 7 mm on vertical panel, operating position: vertical y 4 screws diameter: 7 mm on horizontal panel with derating to 90 %		
Output Coupling	Grounding of secondary Series by internal jumper Parallel		
Operating Altitude	3000 m		
Electrical Insulation Class	Class F		
Width	150.0 mm		
Height	156.0 mm		
Depth	145.0 mm		
Net Weight	13.58 kg		

Environment

Product Certifications	EAC UR DNV-GL	
Standards	UL 506	
Ip Degree Of Protection	IP20	
Environmental Characteristic	EMC conforming to EN 62041 Safety conforming to EN 61558-1 Safety conforming to EN 61558-2-4	
Ambient Air Temperature For Storage	-4080 °C	
Relative Humidity	095 % during operation	
Overvoltage Category	Class I conforming to VDE 0106-1	
Dielectric Strength	3200 V between input and ground 3200 V between output and ground 5100 V between input and output	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	21.000 cm
Package 1 Width	31.000 cm
Package 1 Length	30.000 cm
Package 1 Weight	14.406 kg
Unit Type Of Package 2	P06
Number Of Units In Package 2	4
Package 2 Height	75.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	66.124 kg

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

②	Mercury Free	
	Rohs Exemption Information	Yes
	Pvc Free	


Certifications & Standards

Reach Regulation	REACh Declaration			
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)			
China Rohs Regulation	China RoHS declaration			
Environmental Disclosure	Product Environmental Profile			
Circularity Profile	No need of specific recycling operations Circularity Profile			

ABT7PDU100G

Dimensions Drawings

Dimensions



Dimensions in mm

а	b	С	G	J	Ø
150	145	156	122	134	7

Dimensions in in.


а	b	С	G	J	Ø
5.90	5.71	6.14	4.80	5.28	0.27

Product datasheet


ABT7PDU100G


Connections and Schema

Internal Scheme



Primary Voltage Wiring





Secondary Voltage Wiring

