



## MATERIAL FACT SHEET

### 311899 AJ65VBTS32-32DT

#### General Data

Product Hierarchy	IAD50305
	Modular PLC
	CC-LINK
Ext. Material Group	10 STANDARD ITEM
ABC Indicator	C (Non-Stock Material / Make-to-Order)

e-shop: [https://mitsubishi-electric-eshop.mee.com/mee/FA\\_IA/EUR/en/p/000000000000311899](https://mitsubishi-electric-eshop.mee.com/mee/FA_IA/EUR/en/p/000000000000311899)

#### FA-MOD PLC: Digital I/O Module

Series	CC-LINK
Type	REMOTE I/O COMBINED MODULE
Power Supply (V)	24
Current Type	DC
Occupied Stations	1
Integrated Digital Inputs	16
Integrated Digital Outputs	16
Rated Input Voltage (VDC)	24
Rated Load Voltage (VDC)	12-24
Output Type	TRANSISTOR
Output Logic	SINK
Wiring	SPRING CLAMP
Int. Current Consumption (A)	0,05

#### Product Dimensions & Weight

Width (mm)	222
Height (mm)	50
Depth (mm)	51,5
Weight (kg)	0,41

#### Logistic Dimensions & Gross Weight

Length (cm)	26,0
Width (cm)	8,0
Height (cm)	8,0
Gross Weight (kg)	0,526
Volume (cdm)	1,664

#### Stock Data

Planned Delivery Time (Days)	75
------------------------------	----

#### Life Cycle

Sales Start	04.04.2017
Predecessor	No Predecessor

#### Additional Product Information

Battery included	NO
------------------	----

#### Export Data

Commodity Code	85389099
Legal Control (Dual Use List)	Not Listed
Country of Origin	Japan (JP)
Preference Status (Supplier Declaration)	Non EU

#### Environmental

REACH Limit Exceeded	YES
REACH Substance CAS Number	<a href="#">1303-86-2</a>

REACH Substance CAS Number (2)	<a href="#">7439-92-1</a>
Dangerous Goods Class	NO
Dangerous Goods Identifier	NO
WEEE	B2B

### Conformity

CE	COMPLIANT
UL/cUL	COMPLIANT
EAC	NON-COMPLIANT
UKCA	COMPLIANT

### Documentation & Media Data

Manual URL Indicator	<a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=bltdae25c2bd5f2ff94&amp;q=AJ65VBTS32-32DT&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=bltdae25c2bd5f2ff94&amp;q=AJ65VBTS32-32DT&amp;doc-lang=en</a>
Certificates URL Indicator	<a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt8050dd1408c11cc2&amp;q=AJ65VBTS32-32DT&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt8050dd1408c11cc2&amp;q=AJ65VBTS32-32DT&amp;doc-lang=en</a>
CAD URL Indicator	<a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt26ecc97a31a841c1&amp;q=AJ65VBTS32-32DT&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt26ecc97a31a841c1&amp;q=AJ65VBTS32-32DT&amp;doc-lang=en</a>

### Product Packaging

Cardboard (g)	120
Other paper (g)	0
Aluminum (g)	0
Steel (g)	0
Styrofoam (g)	0
Other plastic (g)	3
Wood (g)	0
Glass (g)	0
Others (g)	0

### Compatible products

Material	Description / Price List Text / Classification
<a href="#">168347</a>	A6CON-L5P 5-pin connector for CC-Link remote I/O, 10 pieces Class 100100215: FA-MOD PLC: Other Option
<a href="#">168348</a>	A6CON-PW5P Connector for CC-Link Remote I/O; Resistance 110 Ohm; Set (10 pcs) Class 100100215: FA-MOD PLC: Other Option
280085	A6CON-LJ5P CC-link communication for online connector (5 pcs) Class 100100215: FA-MOD PLC: Other Option
<a href="#">280087</a>	A6CON-TR11N Termination resistor (110Ω) with built-in CC-link one-touch connector plug; 1pcs Class 100100215: FA-MOD PLC: Other Option
<a href="#">280088</a>	A6CON-PW5P-SOD Power FG for one-touch connector plug; (10 pcs) Class 100100215: FA-MOD PLC: Other Option