

Breaker BQD 3P 60A 347/600VAC 10kA CSA

General technical data	
number of poles	3
suitability for operation	CONSTRUCTION
Electricity	
continuous current rated value	60 A
supply voltage frequency rated value 50/60 Hz	Yes
Environmental conditions	
ambient temperature during operation maximum	40 °C
Model	
product brand name	Siemens
special product feature	PANELBOARD MOUNT
type of electrical connection	LOW TAB
Mechanical Design	
depth [in]	4 in
design of the overload release	THERMAL MAGNETIC TRIP UNIT
design of the product	BQD
height [in]	2.9 in
material of the enclosure	MOLDED CASE CIRCUIT BREAKER
size of the circuit-breaker	100A
width [in]	3 in
General product approval	
standard	UL 489 CSA-C22.2
General Product Approval	



[Confirmation](#)



EG-Konf.



UL



EMV	For use in hazardous locations	Test Certificates	Marine / Shipping
-----	--------------------------------	-------------------	-------------------



RCM

[KC](#)



ATEX



IECEX

[Type Test Certificates/Test Report](#)



ABS

Marine / Shipping	other	Environment
-------------------	-------	-------------



BUREAU
VERITAS



LRS



PRS

[Confirmation](#)

Siemens
EcoTech



EPD

Environment

[Environmental Confirmations](#)

