Range of product	Acti9
Product name	Acti9 MIN
Device short name	MINp
Product or component type	Silent electronic timer
Product compatibility	Mechanical compatibility with electrical comb busbars
Function available	Switch-off warning
Colour tint	White (RAL 9003)

#### mplementary

Complementary		
Device application	Building	
Load type	Fluorescent lamp 22 x electronic ballast 1500 VA Fluorescent lamp 22 x electronic ballast 23 W 230 V AC halogen lamp 3600 W 230 V AC incandescent lamp 3600 W Fluorescent lamp 24 x electronic ballast 15 W Fluorescent lamp 27 x electronic ballast 11 W Fluorescent lamp 34 x electronic ballast 7 W Dual mounted fluorescent tubeconventional ballast 3600 VA Fluorescent tubeelectronic ballast 1000 VA Non-corrected fluorescent tubeconventional ballast 3600 VA Parallel-corrected fluorescent tubeconventional ballast 1200 VA Serial-corrected fluorescent tubeconventional ballast 3600 VA	
Power consumption in VA	6 VA	
Maximum switching current	16 A - 230 V AC pf = 1	
[Ue] rated operational voltage	230 V AC +10 % -15 % at 50/60 Hz	
Time delay	Adjustable from 0.5 to 20 minutes	
Mounting support	DIN rail	
9 mm pitches	2	
Connections - terminals	Screw terminals - <= 6 mm²	
Electrical insulation class	Class II	
Width	18 mm	
Height	89 mm	
Depth	66 mm	
Product weight	103 g	

### **Environment**

Ambient air temperature for operation	-2550 °C
IP degree of protection	IP20 B

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.2 cm
Package 1 Width	7.0 cm
Package 1 Length	10.0 cm
Package 1 Weight	100.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	130
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	13.877 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

## **Contractual warranty**

Warranty 18 months

## Recommended replacement(s)