



Contactor relay, 24 V DC, N/O = Normally open: 2 N/O, N/C = Normally closed: 2 NC, Screw terminals, DC operation

Part no. DILER-22-G(24VDC)

010042

**EL Number
(Norway) 4130354**

| General specifications | | |
|--|--|---|
| Product name | | Eaton Moeller® series DILER Control relay |
| Part no. | | DILER-22-G(24VDC) |
| EAN | | 4015080100423 |
| Product Length/Depth | | 54 millimetre |
| Product height | | 58 millimetre |
| Product width | | 45 millimetre |
| Product weight | | 0.206 kilogram |
| Certifications | | CSA CSA File No.: 012528 CSA Class No.: 3211-03 EN 60947-5-1 IEC/EN 60947-4-1 IEC/EN 60947 UL File No.: E29184 UL Category Control No.: NKCR VDE 0660 CE UL 508 CSA-C22.2 No. 14-05 UL |
| Product Tradename | | DILER |
| Product Type | | Control relay |
| Product Sub Type | | None |
| Catalog Notes | | Coil terminal markings according to EN 50005 Contact numbers according to EN 50011 Rated operational current: Switch-on and switch-off conditions based on DC-13, time constant as specified. |
| Features & Functions | | |
| Features | | Positive operating contacts to EN 60947-5-1 appendix L, including auxiliary contact module |
| Fitted with: | | Interlocked opposing contacts |
| General information | | |
| Application | | Contactor relays |
| Degree of protection | | IP20 |
| Lifespan, mechanical | | 20,000,000 Operations (DC operated) |
| Mounting method | | DIN-rail/screw |
| Mounting position | | As required (except vertical with terminals A1/A2 at the bottom) |
| Operating frequency | | 9000 Operations/h |
| Overvoltage category | | III |
| Pollution degree | | 3 |
| Product category | | DILER Mini-contactors |
| Protection | | Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) |
| Rated impulse withstand voltage (Uimp) | | 6000 V AC |
| Shock resistance | | 10 g, N/O auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 8 g, N/C auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms |
| Voltage type | | DC |
| Climatic environmental conditions | | |
| Ambient operating temperature - min | | -25 °C |
| Ambient operating temperature - max | | 50 °C |
| Ambient operating temperature (enclosed) - min | | -25 °C |
| Ambient operating temperature (enclosed) - max | | 40 °C |

| | | | |
|---|--|--|---|
| Climatic proofing | | | Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30 |
| Terminal capacities | | | |
| Terminal capacity (flexible with ferrule) | | | 1 x (0.75 - 1.5) mm ² 2 x (0.75 - 1.5) mm ² |
| Terminal capacity (solid) | | | 1 x (0.75 - 2.5) mm ² 2 x (0.75 - 2.5) mm ² |
| Terminal capacity (solid/stranded AWG) | | | 18 - 14 1 x (18 - 14) 2 x (18 - 14) |
| Stripping length (main cable) | | | 8 mm |
| Screw size | | | M3.5, Terminal screw |
| Screwdriver size | | | 2, Terminal screw, Pozidriv screwdriver 0.8 x 5.5/1 x 6 mm, Terminal screw, Standard screwdriver |
| Tightening torque | | | 1.2 Nm, Screw terminals |
| Electrical rating | | | |
| Rated operational voltage (Ue) at AC - max | | | 600 V |
| Rated insulation voltage (Ui) | | | 690 V |
| Rated operational current (Ie) | | | 2.5 A at 24 V, DC L/R ≤ 15 ms (with 1 contact in series) 2.5 A at 60 V, DC L/R ≤ 15 ms (with 2 contacts in series) 0.5 A at 220 V, DC L/R ≤ 15 ms (with 3 contacts in series) 1.5 A at 110 V, DC L/R ≤ 15 ms (with 3 contacts in series) 10 A |
| Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V | | | 6 A |
| Rated operational current (Ie) at AC-15, 380 V, 400 V, 415 V | | | 3 A |
| Rated operational current (Ie) at AC-15, 500 V | | | 1.5 A |
| Safe isolation | | | 300 V AC, Between coil and auxiliary contacts, According to EN 61140 300 V AC, Between auxiliary contacts, According to EN 61140 |
| Short-circuit rating | | | |
| Short-circuit protection rating | | | 10 A fast, 500V, Maximum fuse, Short-circuit rating without welding, Contacts |
| Short-circuit protection rating without welding | | | 6 A gG/gL, 500 V, Max. Fuse, Contacts |
| Switching capacity | | | |
| Switching capacity (auxiliary contacts, general use) | | | 0.5 A, 250 V DC, (UL/CSA) 10 A, 600 V AC, (UL/CSA) |
| Switching capacity (auxiliary contacts, pilot duty) | | | P300, DC operated (UL/CSA) A600, AC operated (UL/CSA) |
| Magnet system | | | |
| Duty factor | | | 100 % |
| Pick-up voltage | | | 0.7 - 1.3 V DC x Uc (at 24 V: without auxiliary contact module and at ambient air temperature + 40 °C) 0.85 - 1.3 V DC x Uc |
| Power consumption (pick-up) at DC | | | 2.3 W |
| Power consumption (sealing) at DC | | | 2.3 W |
| Rated control supply voltage (Us) at AC, 50 Hz - min | | | 0 V |
| Rated control supply voltage (Us) at AC, 50 Hz - max | | | 0 V |
| Rated control supply voltage (Us) at AC, 60 Hz - min | | | 0 V |
| Rated control supply voltage (Us) at AC, 60 Hz - max | | | 0 V |
| Rated control supply voltage (Us) at DC - min | | | 24 V |
| Voltage tolerance | | | Smoothed DC, three-phase bridge rectifiers or smoothed double-wave rectification |
| Rated control supply voltage (Us) at DC - max | | | 24 V |
| Switching time (DC operated, make contacts, closing delay) - min | | | 26 ms |
| Switching time (DC operated, make contacts, closing delay) - max | | | 35 ms |
| Switching time (DC operated, make contacts, opening delay) - min | | | 15 ms |
| Switching time (DC operated, make contacts, opening delay) - max | | | 25 ms |
| Switching time (DC operated, N/O, with auxiliary contact module, closing delay) | | | 70 ms |
| Contacts | | | |
| Code number | | | 22E |
| Control circuit reliability | | | < 2 λ, < 1 failure at 100,000,000 Operations (at U# = 24 V DC, Umin = 17 V, Imin = 5.4 mA) |
| Number of auxiliary contacts (change-over contacts) | | | 0 |

| | | |
|--|--|--|
| Number of auxiliary contacts (normally closed contacts) | | 2 |
| Number of auxiliary contacts (normally open contacts) | | 2 |
| Number of contacts (normally closed contacts) | | 2 |
| Number of contacts (normally open contacts) | | 2 |
| Design verification | | |
| Equipment heat dissipation, current-dependent P _{vid} | | 0 W |
| Heat dissipation capacity P _{diss} | | 0 W |
| Heat dissipation per pole, current-dependent P _{vid} | | 0.4 W |
| Rated operational current for specified heat dissipation (I _n) | | 6 A |
| Static heat dissipation, non-current-dependent P _{vs} | | 2.3 W |
| 10.2.2 Corrosion resistance | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | Meets the product standard's requirements. |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | Meets the product standard's requirements. |
| 10.2.5 Lifting | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | | Meets the product standard's requirements. |
| 10.3 Degree of protection of assemblies | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | Is the panel builder's responsibility. |
| 10.9.2 Power-frequency electric strength | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | Is the panel builder's responsibility. |
| 10.10 Temperature rise | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 Electromagnetic compatibility | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

Technical data ETIM 9.0

| | | |
|---|---|----------------|
| Low-voltage industrial components (EG000017) / Contactor relay (EC000196) | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Contactor relay (ecl@ss13-27-37-10-01 [AAB716019]) | | |
| Rated control supply voltage AC 50 Hz | V | 0 - 0 |
| Rated control supply voltage AC 60 Hz | V | 0 - 0 |
| Rated control supply voltage DC | V | 24 - 24 |
| Voltage type for actuating | | DC |
| Rated operation current | A | 10 |
| Rated operation current I _e , 400 V | A | 3 |
| Mounting method | | DIN-rail/screw |
| With LED indication | | No |
| Suitable for manual operation | | No |
| Interface | | No |
| Number of auxiliary contacts as normally closed contact | | 2 |
| Number of auxiliary contacts as normally open contact | | 2 |
| Number of auxiliary contacts as normally closed contact, delayed switching | | 0 |
| Number of auxiliary contacts as normally open contact, leading | | 0 |
| Number of auxiliary contacts as change-over contact | | 0 |
| Operating voltage AC 50 Hz | V | 17 - 500 |
| Operating voltage AC 60 Hz | V | 17 - 500 |
| Operating voltage DC | V | 24 - 220 |

| | | |
|-----------------------------------|----|------------------|
| Voltage type (operating voltage) | | AC/DC |
| Rated switch current | A | 10 |
| Connection type auxiliary circuit | | Screw connection |
| Width | mm | 45 |
| Height | mm | 58 |
| Depth | mm | 54 |