
Product data sheet

Specifications



Main

Product or Component Type	Circuit breaker
Trip Unit Technology	Thermal-magnetic

Complementary

Line Rated Current90 ANumber of Poles3PBreaking capacity codeAMounting ModeUnit mountMagnetic Hold Current900 AMagnetic Tripping Current1700 AElectrical connectionLugs, load Lugs, lineTerminal identifierAL100FAPhase connectionABCHeight6.4 in (162.6 mm)Width4.5 in (114.3 mm)			
Breaking capacity code A Mounting Mode Unit mount Magnetic Hold Current 900 A Magnetic Tripping Current 1700 A Electrical connection Lugs, load Lugs, line Terminal identifier AL100FA Phase connection ABC Height 6.4 in (162.6 mm)			
Mounting Mode Unit mount Magnetic Hold Current 900 A Magnetic Tripping Current 1700 A Electrical connection Lugs, load Lugs, line Terminal identifier AL100FA Phase connection ABC Height 6.4 in (162.6 mm)	3P		
Magnetic Hold Current 900 A Magnetic Tripping Current 1700 A Electrical connection Lugs, load Lugs, line Terminal identifier AL100FA Phase connection ABC Height 6.4 in (162.6 mm)			
Magnetic Tripping Current 1700 A Electrical connection Lugs, load Lugs, line Terminal identifier AL100FA ABC Height 6.4 in (162.6 mm)			
Electrical connection Lugs, load Lugs, line Terminal identifier AL100FA Phase connection ABC Height 6.4 in (162.6 mm)			
Lugs, line Terminal identifier AL100FA Phase connection ABC Height 6.4 in (162.6 mm)			
Phase connection ABC Height 6.4 in (162.6 mm)			
Height 6.4 in (162.6 mm)			
Width 4.5 in (114.3 mm)	6.4 in (162.6 mm)		
	4.5 in (114.3 mm)		
Depth 4.13 in (104.90 mm)			
Circuit breaker application HACR rated	HACR rated		

Environment

Certifications

UL Listed CSA

Ordering and shipping details

Category	US10DE200902	
Discount Schedule	0DE2	
GTIN	785901423423	
Returnability	Yes	
Country of origin	US	

Packing Units

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	6.00 in (15.24 cm)	
Package 1 Width	6.00 in (15.24 cm)	
Package 1 Length	10.00 in (25.4 cm)	
Package 1 Weight	4.65 lb(US) (2.11 kg)	

Contractual warranty

Warranty

18 months

Lenvironmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability \geq

${\mathcal Q}$ Environmental footprint		
Environmental Disclosure	Product Environmental Profile	
Use Better		
ℬ Materials and Substances		
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
China RoHS Regulation	China RoHS declaration	
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause Birth Defects or other reproductive harm.For more information go to www.p65warnings.ca.gov	