

ITY-E-TW020LB-I
ITYS-E 2kVA I 230V ONLU-B CH+S+
Strong points

- Best electrical protection
- Robust and versatile

General characteristics

- True online double conversion technology (VFI)
- Constant output voltage and frequency regulation
- Automatic bypass supplies the loads in the event of overloads or faults
- Compact tower UPS system
- Easy connections via sockets or terminals
- Wide input voltage tolerance
- Manual bypass for periodic or emergency maintenance

Compliance with standards

- EN 62040-1
- EN 62040-2
- CE

Access to resources (ex: manuals)

Compact tower UPS system saves space in the operating environment.

Classification

UNSPSC	39121011
ETIM Class	EC000382
IGCC	4149

Commerce

Description (240 char.)	ITYS-E 2000VA/1600W 230V 50Hz WITH POWERFUL BATTERY CHARGER FOR LONGAUTONOMYFOR LONGANTONOMY EXTERNAL BATTERY ON-LINE DOUBLE CONVERSION (VFI)
Effective date	2015-06-01
Country of origin	CN
Length of the product unit	0.22
Width of the product unit	0.145
Depth of the product unit	0.4
Weight	36.5

Logistics

GTIN/EAN	3596032864057
Customs number	8504409590
Weight of the packing unit	36.5
Length of the packing unit	0.4
Width of the packing unit	0.145
Depth of the packing unit	0.22

Technical Characteristics

Depth	400
Height	220
In/out	1/1
Output voltage	230
Rated frequency	50/50
Width	145
Sn	2
Pn	1.6
Conf	C1
Input voltage	230
Rate (min)	2
Rate (max)	2
Configuration	UPS Single Unit(s) with Bypass