

# Product data sheet

Specifications



## Contactor, EasyPact TVS, 3P(3NO), AC-3, <=440V, 200A, 24V AC coil, 50Hz

LC1E200B5

### Main

|                                |  |
|--------------------------------|--|
| Range                          | EasyPact   |
| Product or component type      | Contactor  |
| Device short name              | LC1E   |
| Contactor application          | Resistive load<br>Motor control  |
| Utilisation category           | AC-1<br>AC-3   |
| Poles description              | 3P   |
| [Ue] rated operational voltage | Power circuit: <= 690 V AC 50/60 Hz  |
| [Ie] rated operational current | 200 A (at <55 °C) at <= 440 V AC AC-3 for power circuit<br>250 A (at <40 °C) at <= 440 V AC AC-1 for power circuit |
| [Uc] control circuit voltage   | 24 V AC 50 Hz  |

### Complementary

|   |  |
|---|--|
| Motor power kW                              | 55 kW at 220...230 V AC 50/60 Hz (AC-3)<br>90 kW at 380...400 V AC 50/60 Hz (AC-3)<br>100 kW at 415 V AC 50/60 Hz (AC-3)<br>100 kW at 440 V AC 50/60 Hz (AC-3)<br>110 kW at 500 V AC 50/60 Hz (AC-3)<br>110 kW at 660...690 V AC 50/60 Hz (AC-3) |
| Pole contact composition                    | 3 NO   |
| [Ith] conventional free air thermal current | 250 A (at 55 °C)   |
| Irms rated making capacity                  | 2000 A at 440 V AC for power circuit conforming to IEC 60947-4-1   |
| Rated breaking capacity                     | 1600 A at 440 V for power circuit conforming to IEC 60947  |
| [Icw] rated short-time withstand current    | 1500 A 40 °C - 10 s for power circuit  |
| Associated fuse rating                      | 10 A gG at <= 690 V coordination type 1 for control circuit conforming to IEC 60947-5-1<br>315 A gG at <= 690 V coordination type 1 for power circuit  |
| Average impedance                           | 0.33 mOhm - Ith 250 A 50 Hz for power circuit  |
| Power dissipation per pole                  | 13 W AC-3<br>21 W AC-1   |
| [Ui] rated insulation voltage               | 690 V conforming to IEC 60947-4-1  |
| Overvoltage category                        | III  |
| Pollution degree                            | 3  |

|  |  |
|--|--|
| [Uimp] rated impulse withstand voltage | 8 kV coil not connected to the power circuit conforming to IEC 60947   |
| Mechanical durability                  | 500000 cycles  |
| Electrical durability                  | 500000 cycles AC-3<br>200000 cycles AC-1   |
| Control circuit type                   | AC at 50 Hz  |
| Control circuit voltage limits         | 0.85...1.1 Uc (55 °C):operational 50 Hz<br>0.35...0.55 Uc (55 °C):drop-out 50 Hz   |
| Inrush power in VA                     | 805 VA 50 Hz cos phi 0.3 (at 20 °C)<br>970 VA 60 Hz cos phi 0.3 (at 20 °C)   |
| Hold-in power consumption in VA        | 55 VA 50 Hz cos phi 0.3 (at 20 °C)<br>66 VA 60 Hz cos phi 0.3 (at 20 °C)   |
| Heat dissipation                       | 18...24 W for control circuit  |
| Operating time                         | 20...35 ms on closing<br>7...15 ms on opening  |
| Maximum operating rate                 | 1200 cyc/h 55 °C   |
| Connections - terminals                | Control circuit: screw clamp terminals 1 1...4 mm² - cable stiffness: flexible without cable end<br>Control circuit: screw clamp terminals 2 1...4 mm² - cable stiffness: flexible without cable end<br>Control circuit: screw clamp terminals 2 1...2.5 mm² - cable stiffness: flexible with cable end<br>Control circuit: screw clamp terminals 1 1...4 mm² - cable stiffness: solid without cable end<br>Control circuit: screw clamp terminals 2 1...4 mm² - cable stiffness: solid without cable end<br>Control circuit: screw clamp terminals 1 1...2.5 mm² - cable stiffness: flexible with cable end<br>Power circuit: cable with lug - external diameter: 150 mm<br>Power circuit: bars 2 - busbar cross section: 3 x 25 mm |
| Tightening torque                      | Control circuit: 1.2 N.m<br>Power circuit: 18 N.m  |
| Minimum switching voltage              | 17 V for control circuit   |
| Minimum switching current              | 5 mA for control circuit   |
| Insulation resistance                  | > 10 MOhm for control circuit  |
| Non-overlap time                       | 1.5 ms on energisation guaranteed between NC and NO contact<br>1.5 ms on de-energisation guaranteed between NC and NO contact  |
| Mounting support                       | Plate  |

## Environment

|   |  |
|---|--|
| Standards   | IEC 60947-4-1<br>IEC 60947-5-1<br>IEC 60947-1  |
| Product certifications                                | EAC<br>CE  |
| IP degree of protection                               | IP2X conforming to IEC 60529   |
| Protective treatment                                  | TH (pollution degree 3) conforming to IEC 60068-2-30 test Db   |
| Permissible ambient air temperature around the device | -20...70 °C at Uc<br>-60...80 °C storage<br>-5...55 °C operation   |
| Operating altitude                                    | 3000 m without derating  |
| Fire resistance                                       | 850 °C conforming to IEC 60695-2-1   |
| Mechanical robustness                                 | Vibrations contactor open (1.5 Gn, 5...300 Hz)<br>Vibrations contactor closed (3 Gn, 5...300 Hz)<br>Shocks contactor open (6 Gn for 11 ms)<br>Shocks contactor closed (7 Gn for 11 ms) |
| Height  | 174 mm   |
| Width   | 168.5 mm   |
| Depth   | 181 mm   |
| Net weight  | 4.6 kg   |

Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 22 cm     |
| Package 1 Width              | 20 cm     |
| Package 1 Length             | 25 cm     |
| Package 1 Weight             | 5.1 kg    |
| Unit Type of Package 2       | P06       |
| Number of Units in Package 2 | 8         |
| Package 2 Height             | 77 cm     |
| Package 2 Width              | 80 cm     |
| Package 2 Length             | 60 cm     |
| Package 2 Weight             | 55.004 kg |
| Unit Type of Package 3       | S06       |
| Number of Units in Package 3 | 12        |
| Package 3 Height             | 73.5 cm   |
| Package 3 Width              | 60 cm     |
| Package 3 Length             | 80 cm     |
| Package 3 Weight             | 74.2 kg   |

Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a>  |
| Mercury free               | Yes   |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information       |
| RoHS exemption information | <a href="#">Yes</a>   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Recommended replacement(s)