

Product datasheet

Specifications



EasyPact TVS contactor 4P CTR 25A AC1(4NO)415V 50Hz WB

LC1E40004N5WBIN

Main

| | |
|--------------------------------|--|
| Range | EasyPact |
| Product or component type | Contactor |
| Device short name | LC1E |
| Contactor application | Resistive load |
| Utilisation category | AC-1 |
| Poles description | 4P |
| [Ue] rated operational voltage | Power circuit: <= 690 V AC 50/60 Hz |
| [Ie] rated operational current | 75 A (at <40 °C) at <= 415 V AC AC-1 for power circuit |
| [Uc] control circuit voltage | 415 V AC 50 Hz |

Complementary

| | |
|--|--|
| Pole contact composition | 4 NO |
| Irms rated making capacity | 400 A at 440 V AC for power circuit conforming to IEC 60947-4-1 |
| Rated breaking capacity | 320 A at 440 V for power circuit conforming to IEC 60947 |
| [Icw] rated short-time withstand current | 320 A 40 °C - 10 s for power circuit 165 A 40 °C - 60 s for power circuit 72 A 40 °C - 600 s for power circuit |
| Associated fuse rating | 80 A gG at <= 690 V coordination type 1 for power circuit |
| Average impedance | 1.5 mOhm - Ith 75 A 50 Hz for power circuit |
| Power dissipation per pole | 5.4 W AC-1 |
| [Ui] rated insulation voltage | 690 V conforming to IEC 60947-4-1 |
| Overvoltage category | III |
| Pollution degree | 3 |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to IEC 60947 |
| Mechanical durability | 5 Mcycles |
| Electrical durability | 0.35 Mcycles AC-1 |
| Control circuit type | AC at 50 Hz wide range |
| Control circuit voltage limits | 0.3...0.6 Uc (55 °C):drop-out 50 Hz 0.7...1.25 Uc (55 °C):operational 50 Hz |
| Inrush power in VA | 160 VA 50 Hz cos phi 0.75 (at 20 °C) |

| | |
|---------------------------------|--|
| Hold-in power consumption in VA | 15 VA 50 Hz cos phi 0.3 (at 20 °C) |
| Heat dissipation | 6...10 W for control circuit |
| Operating time | 20...26 ms on closing 8...12 ms on opening |
| Maximum operating rate | 1200 cyc/h 60 °C |
| Connections - terminals | Control circuit: screw clamp terminals 1 1...4 mm ² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 1...4 mm ² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 1 1...4 mm ² - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 2 1...2.5 mm ² - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 1 2.5...25 mm ² - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 2 2.5...10 mm ² - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 1...4 mm ² - cable stiffness: solid Control circuit: screw clamp terminals 2 1...4 mm ² - cable stiffness: solid Power circuit: screw clamp terminals 1 2.5...25 mm ² - cable stiffness: solid Power circuit: screw clamp terminals 2 2.5...16 mm ² - cable stiffness: solid |
| Tightening torque | Control circuit: 1.2 N.m Power circuit: 5 N.m |
| Auxiliary contact composition | Without |
| Mounting support | Plate DIN rail |

Environment

| | |
|---|--|
| Standards | IEC 60947-5-1 IEC 60947-4-1 |
| Product certifications | EAC |
| IP degree of protection | IP20 conforming to IEC 60529 |
| Protective treatment | TH conforming to IEC 60068 |
| Permissible ambient air temperature around the device | -20...70 °C at Uc -60...80 °C storage -5...55 °C operation |
| Operating altitude | 3000 m |
| Fire resistance | 850 °C conforming to IEC 60695-2-1 |
| Mechanical robustness | Vibrations contactor open (1.5 Gn, 5...300 Hz) Vibrations contactor closed (3 Gn, 5...300 Hz) Shocks contactor open (6 Gn for 11 ms) Shocks contactor closed (7 Gn for 11 ms) |
| Height | 127 mm |
| Width | 85 mm |
| Depth | 110 mm |
| Net weight | 1.3 kg |

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 11 cm |
| Package 1 Width | 8.5 cm |
| Package 1 Length | 12.7 cm |
| Package 1 Weight | 1300 g |
| Unit Type of Package 2 | S03 |
| Number of Units in Package 2 | 6 |
| Package 2 Height | 30 cm |
| Package 2 Width | 30 cm |
| Package 2 Length | 40 cm |

| | |
|------------------------------|---------|
| Package 2 Weight | 9.4 kg |
| Unit Type of Package 3 | P06 |
| Number of Units in Package 3 | 48 |
| Package 3 Height | 150 cm |
| Package 3 Width | 60 cm |
| Package 3 Length | 80 cm |
| Package 3 Weight | 77.2 kg |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |

Recommended replacement(s)