

Product datasheet

Specifications



communication module - for TeSys U - 24 V DC

LULC033

Main

Range	TeSys
Device short name	LUL
Product or component type	Communication module
Product compatibility	LUCL LUCC LUCB LUCM LUCA LUCD
Device application	Communication
Range compatibility	TeSys (TeSys U) LUB non reversing power base TeSys (TeSys U) LU2B reversing power base

Complementary

Main function available	Communication module
Mounting mode	Plug-in
Mounting location	Front side
Physical interface	RS485 multidrop
Bus type	Modbus
Cable connector type	RJ45 front panel
Communication port protocol	Modbus RTU
Addressing	0...31
Transmission rate	19200 bit/s
Return time	30 ms
Number of inputs	2
Logic input	Positive at 24 V DC - 7 mA
Response time	10 ms +/- 30 % change to state 0 10 ms +/- 30 % change to state 1
Input type	Resistive
Number of outputs	2 dedicated to starter-controller coil operation 1
[Us] rated supply voltage	24 V DC
Output current	<= 500 mA

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Protection type	GG fuse 1 A
Switching current capacity	0.5 mA at 24 V
Local signalling	3 LEDs front panel
Connection pitch	3.81 mm
Connections - terminals	Screw clamp terminals 1 cable(s) 0.14...1 mm²flexible without cable end Screw clamp terminals 1 cable(s) 0.14...1 mm²rigid without cable end Screw clamp terminals 1 cable(s) 0.25...0.5 mm²flexible with cable end Screw clamp terminals 1 cable(s) 0.25...1 mm²flexible with cable end Screw clamp terminals 2 cable(s) 0.14...0.5 mm²rigid without cable end Screw clamp terminals 2 cable(s) 0.14...0.75 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.25...0.34 mm²flexible with cable end Screw clamp terminals 2 cable(s) 0.5 mm²flexible with cable end
Associated cable type	AWG 26...AWG 16
Tightening torque	0.2...0.25 N.m2.5 mm
Net weight	0.08 kg

Environment

Ambient air temperature for operation	-25...55 °C
IP degree of protection	IP20 conforming to IEC 60529

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.9 cm
Package 1 Width	11.3 cm
Package 1 Length	4.9 cm
Package 1 Weight	85.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	35
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	3.293 kg

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)