

Product datasheet

Specifications



busbar Easypact - 250 A - 8 ways

EZB250W08

⚠ Discontinued on: 07 December 2020

⚠ Discontinued

Main

Range of product	EasyPact
Range	EasyPact
Device short name	busbar
Product or component type	Busbar
Device application	Connection
Range compatibility	EasyPact EasyPact EZB circuit breaker
[In] rated current	250 A
Number of ways	8 ways

Complementary

[Ui] rated insulation voltage	690 V AC 50/60 Hz
[Ue] rated operational voltage	550 V AC 50/60 Hz
Number of devices	12 (2P) 24 (1P) 8 (3P)
Busbar extension	Without
[Icw] rated short-time withstand current	30 kA for 1 s
Height	418.5 mm
Width	416 mm
Depth	82.5 mm

Environment

Standards	IEC 60439
-----------	-----------

Offer Sustainability

REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes

China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)