



standard motor mechanism module MT100/160, ComPact NSX100/160, 110/130 VAC 50/60 Hz

LV429433

Main

MT250
Motor mechanism
Automatic spring charging
ComPacT new generation ComPacT NSX100 new generation ComPacT new generation ComPacT NSX160 new generation ComPact ComPact NSX100 ComPact ComPact NSX160 ComPact ComPacT NSX DC new generation NSX100 DC ComPact ComPacT NSX DC new generation NSX160 DC ComPact Compact NSX100 DC ComPact Compact NSX100 DC ComPact Compact NSX160 DC PowerPact Multistandard PowerPact Multistandard EasyPact EasyPact CVS250 PowerPact PowerPact J PowerPact PowerPact H
Standard
110130 V AC 50/60 Hz
Fixed
100 A 160 A

Complementary

Control signal type	Maintained Impulse
Circuit breaker response time	< 700 ms open < 80 ms closed
Maximum operating frequency	4 per minute
Maximum power consumption in VA	500 VA closing 500 VA opening
Provided equipment	SDE adaptor
Locking options description	Padlocking in OFF position 1 to 3 padlocks Ø 5 to Ø 8

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12 cm
Package 1 Width	10.5 cm

Package 1 Length	17.3 cm
Package 1 Weight	1.386 kg
Unit Type of Package 2	S04
Number of Units in Package 2	15
Package 2 Height	30 cm
Package 2 Width	40 cm
Package 2 Length	60 cm
Package 2 Weight	21.661 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty 18 months

Recommended replacement(s)