

# Product datasheet

Specifications



Vigi add-on protection module,  
Compact NSX 250, EasyPact CVS  
250, MH type, 200 VAC to 440 VAC,  
30 mA to 10 A, 3 poles

LV431535

⚠ Discontinued

⚠ Discontinued on: 18 November 2021

⚠ End-of-service on: 03 March 2022

## Main

Range of product	ComPact NSX100...250
Range	ComPact
Product or component type	Vigi add-on
Device application	Wiring
Range compatibility	ComPact ComPact NSX250 circuit breaker EasyPact EasyPact CVS250 circuit breaker
Poles description	3P
[In] rated current	250 A
Earth-leakage add-on module name	MH
Earth-leakage protection class	Class A
Residual earth-leakage sensitivity adjustment type	Adjustable 5 settings
Earth-leakage sensitivity	0.03 A 0.3 A 1 A 3 A 10 A
Residual earth-leakage time delay adjustment type	Adjustable 4 settings
[Δt] residual earth-leakage time delay adjustment	310 ms 0 ms 60 ms 150 ms

## Complementary

Network type	AC
Network frequency	50/60 Hz
[Ue] rated operational voltage	200...440 V AC 50/60 Hz conforming to IEC 60947-2
Earth-leakage protection	With
Maximum breaking time	800 ms
Overvoltage category	Class II

Environment

Electrical shock protection class	Class II
Standards	IEC 60947-2

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)