



## MATERIAL FACT SHEET

### 238090 LY42NT1P

#### General Data

Product Hierarchy	IAD510
	Modular PLC
	L-Serie
Ext. Material Group	10 STANDARD ITEM
ABC Indicator	C (Non-Stock Material / Make-to-Order)

e-shop: [https://mitsubishi-electric-eshop.mee.com/mee/FA\\_IA/EUR/en/p/000000000000238090](https://mitsubishi-electric-eshop.mee.com/mee/FA_IA/EUR/en/p/000000000000238090)

#### FA-MOD PLC: Digital Output Module

Series	MELSEC-L SERIES
Type	TRANSISTOR OUTPUT (SINK)
Power Supply (V)	12-24
Current Type	DC
Occupied I/O Points on PLC	64
Integrated Digital Outputs	64
Output Type	TRANSISTOR
Output Logic	SINK
Rated Load Voltage (VDC)	24
Wiring	CONNECTOR
Int. Current Consumption (A)	0,19

#### Product Dimensions & Weight

Width (mm)	28,5
Height (mm)	90
Depth (mm)	95
Weight (kg)	0,12

#### Logistic Dimensions & Gross Weight

Length (cm)	15,0
Width (cm)	13,0
Height (cm)	6,3
Gross Weight (kg)	0,180
Volume (cdm)	1,229

#### Stock Data

Planned Delivery Time (Days)	136
------------------------------	-----

#### Life Cycle

Sales Start	03.02.2011
Predecessor	No Predecessor

#### Additional Product Information

Battery included	NO
------------------	----

#### Export Data

Commodity Code	85389099
Legal Control (Dual Use List)	Not Listed
Country of Origin	Japan (JP)
Preference Status (Supplier Declaration)	Non EU

#### Environmental

REACH Limit Exceeded	YES
REACH Substance CAS Number	<a href="#">7439-92-1</a>
Dangerous Goods Class	NO
Dangerous Goods Identifier	NO

RoHS Compliance	COMPLIANT
WEEE	B2B

### Conformity

CE	COMPLIANT
UL/cUL	COMPLIANT
EAC	NON-COMPLIANT
UKCA	COMPLIANT

### Documentation & Media Data

Manual URL Indicator	<a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=bltdae25c2bd5f2ff94&amp;q=LY42NT1P&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=bltdae25c2bd5f2ff94&amp;q=LY42NT1P&amp;doc-lang=en</a>
Certificates URL Indicator	<a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt8050dd1408c11cc2&amp;q=LY42NT1P&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt8050dd1408c11cc2&amp;q=LY42NT1P&amp;doc-lang=en</a>
CAD URL Indicator	<a href="https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt26ecc97a31a841c1&amp;q=LY42NT1P&amp;doc-lang=en">https://emea.mitsubishielectric.com/fa/advanced-search?ct=document&amp;doc-cats=blt26ecc97a31a841c1&amp;q=LY42NT1P&amp;doc-lang=en</a>

### Product Packaging

Cardboard (g)	50
Other paper (g)	0
Aluminum (g)	0
Steel (g)	0
Styrofoam (g)	0
Other plastic (g)	0
Wood (g)	0
Glass (g)	0
Others (g)	0

### Compatible products

Material	Description / Price List Text / Classification
<a href="#">202286</a>	FA-CBL05FMV Connection cable; PLC 40-pin I/O connector to 32-point terminal block; 0,5 m Class 100100214: FA-MOD PLC: Cable
<a href="#">227165</a>	FA-CBL10FMV Connection cable; PLC 40-pin I/O connector to 32-point terminal block; 1 m Class 100100214: FA-MOD PLC: Cable
<a href="#">278130</a>	FA-CBL50FMV Connection cable; PLC 40-pin I/O connector to 32-point terminal block; 5 m Class 100100214: FA-MOD PLC: Cable
<a href="#">279750</a>	FA-CBL30FMV Connection cable; PLC 40-pin I/O connector to 32-point terminal block; 3 m Class 100100214: FA-MOD PLC: Cable
<a href="#">308387</a>	FA1-TESV32XY Connector Spring Clamp 32 Point Terminal Conversion Unit Class 100100215: FA-MOD PLC: Other Option
<a href="#">686133</a>	FA-CBL100FMV Connection cable for DC-dedicated distributed type conversion modules; 10 m Class 100100214: FA-MOD PLC: Cable