



EasyLogic PM2X30 - I/O Module - Digital - 2 Inputs + 2 outputs

METSEPM2KDGTLIO22D

Main

Range	Fasul asia
Nange	EasyLogic
Device Short Name	PM2K2DIDO
Product Or Component Type	I/O module
Device Application	Optional expansion module
Range Compatibility	EasyLogic EasyLogic PM2100 PM2130 EasyLogic EasyLogic PM2200 PM2230

Complementary

Switching Frequency	2 Hz digital input
[Ui] Rated Insulation Voltage	2500 V
Number Of Outputs	2 configurable, <= 20 mA
Output Voltage	40 V DC
Input Impedance	110 kOhm
Number Of Inputs	2
Output Impedance	50 Ohm
Voltage State 0 Guaranteed	04 V DC
Voltage State 1 Guaranteed	18.536 V DC
Width	90.5 mm
Depth	14.6 mm
Height	53 mm
Net Weight	50 g
Targeted Country	India

Environment

Ambient Air Temperature For Operation	-1060 °C	
Ambient Air Temperature For Storage	-2570 °C	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	7.2 cm
Package 1 Width	9.6 cm

Package 1 Length	9.6 cm	
Package 1 Weight	0.2 kg	



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information