

**Circuit-breaker, 3p, 25A**

Part no. **NZMH1-A25**
284377
EL Number **4363447**
(Norway)

General specifications		
Product name		Eaton Moeller series NZM molded case circuit breaker thermo-magnetic
Part no.		NZMH1-A25
EAN		4015082843779
Product Length/Depth		84.5 millimetre
Product height		145 millimetre
Product width		90 millimetre
Product weight		1.025 kilogram
Compliances		RoHS conform
Certifications		IEC IEC/EN 60947
Product Tradename		NZM
Product Type		Molded case circuit breaker
Product Sub Type		Thermo-magnetic
Delivery program		
Application		Use in unearthed supply systems at 690 V
Type		Circuit breaker
Circuit breaker frame type		NZM1
Number of poles		Three-pole
Amperage Rating		25 A
Release system		Thermomagnetic release
Features		Protection unit
Special features		Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity I _{cn}) Rated current = rated uninterrupted current: 25 A Terminal capacity hint: Up to 95 mm ² can be connected depending on the cable manufacturer.
Technical Data - Electrical		
Voltage rating		690 V - 690 V
Voltage rating (DC)		450 V DC
Rated insulation voltage (U _i)		690 V AC
Rated impulse withstand voltage (U _{imp}) at auxiliary contacts		6000 V
Rated impulse withstand voltage (U _{imp}) at main contacts		6000 V
Instantaneous current setting (I _i) - min		350 A
Instantaneous current setting (I _i) - max		350 A
Overload current setting (I _r) - min		20 A
Overload current setting (I _r) - max		25 A
Short delay current setting (I _{sd}) - min		0 A
Short delay current setting (I _{sd}) - max		0 A
Short-circuit release non-delayed setting - min		350 A
Short-circuit release non-delayed setting - max		350 A
Rated short-circuit breaking capacity I _{cs} (IEC/EN 60947) at 230 V, 50/60 Hz		100 kA
Rated short-circuit breaking capacity I _{cs} (IEC/EN 60947) at 400/415 V, 50/60 Hz		50 kA
Rated short-circuit breaking capacity I _{cs} (IEC/EN 60947) at 440 V, 50/60 Hz		35 kA
Rated short-circuit breaking capacity I _{cs} (IEC/EN 60947) at 525 V, 50/60 Hz		10 kA
Rated short-circuit breaking capacity I _{cs} (IEC/EN 60947) at 690 V, 50/60 Hz		7.5 kA
Rated short-circuit making capacity I _{cm} at 240 V, 50/60 Hz		220 kA
Rated short-circuit making capacity I _{cm} at 400/415 V, 50/60 Hz		220 kA
Rated short-circuit making capacity I _{cm} at 440 V, 50/60 Hz		154 kA

Rated short-circuit making capacity Icm at 525 V, 50/60 Hz		40 kA
Rated short-circuit making capacity Icm at 690 V, 50/60 Hz		17 kA
Short-circuit total breaktime		< 10 ms
Electrical connection type of main circuit		Frame clamp
Isolation		300 V AC (between the auxiliary contacts) 500 V AC (between auxiliary contacts and main contacts)
Number of operations per hour - max		120
Handle type		Rocker lever
Utilization category		A (IEC/EN 60947-2)
Overvoltage category		III
Pollution degree		3
Lifespan, electrical		10000 operations at 415 V AC-1 7500 operations at 690 V AC-1 10000 operations at 400 V AC-1
Direction of incoming supply		As required
Technical Data - Mechanical		
Mounting Method		DIN rail (top hat rail) mounting optional Fixed Built-in device fixed built-in technique
Degree of protection		IP20 IP20 (basic degree of protection, in the operating controls area)
Degree of protection (IP), front side		IP66 (with door coupling rotary handle) IP40 (with insulating surround)
Degree of protection (terminations)		IP10 (tunnel terminal) IP00 (terminations, phase isolator and strip terminal)
Protection against direct contact		Finger and back-of-hand proof to DIN EN 50274/VDE 0106 part 110
Shock resistance		20 g (half-sinusoidal shock 20 ms)
Number of auxiliary contacts (change-over contacts)		0
Number of auxiliary contacts (normally closed contacts)		0
Number of auxiliary contacts (normally open contacts)		0
Position of connection for main current circuit		Front side
Climatic proofing		Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
Special features		Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity Icn) Rated current = rated uninterrupted current: 25 A Terminal capacity hint: Up to 95 mm² can be connected depending on the cable manufacturer.
Lifespan, mechanical		20000 operations
Technical Data - Mechanical - Terminals		
Standard terminals		Box terminal
Optional terminals		Connection on rear. Screw terminal. Tunnel terminal
Terminal capacity (control cable)		0.75 mm² - 1.5 mm² (2x) 0.75 mm² - 2.5 mm² (1x)
Terminal capacity (aluminum solid conductor/cable)		10 mm² - 16 mm² (1x) direct at switch rear-side connection 16 mm² (1x) at tunnel terminal 10 mm² - 16 mm² (2x) direct at switch rear-side connection
Terminal capacity (aluminum stranded conductor/cable)		25 mm² - 95 mm² (1x) at tunnel terminal 25 mm² - 35 mm² (1x) direct at switch rear-side connection 25 mm² - 35 mm² (2x) direct at switch rear-side connection
Terminal capacity (copper busbar)		Max. 16 mm x 5 mm direct at switch rear-side connection Min. 12 mm x 5 mm direct at switch rear-side connection M6 at rear-side screw connection
Terminal capacity (copper solid conductor/cable)		16 mm² (1x) at tunnel terminal 10 mm² - 16 mm² (1x) at box terminal 6 mm² - 16 mm² (2x) direct at switch rear-side connection 10 mm² - 16 mm² (1x) direct at switch rear-side connection 6 mm² - 16 mm² (2x) at box terminal
Terminal capacity (copper stranded conductor/cable)		6 mm² - 25 mm² (2x) at box terminal 25 mm² (2x) direct at switch rear-side connection 10 mm² - 70 mm² (1x) direct at switch rear-side connection 25 mm² - 95 mm² (1x) at 1-hole tunnel terminal 10 mm² - 70 mm² (1x) at box terminal
Terminal capacity (copper strip)		Max. 9 segments of 9 mm x 0.8 mm at box terminal Min. 2 segments of 9 mm x 0.8 mm at box terminal
Design verification as per IEC/EN 61439 - technical data		

Rated operational current for specified heat dissipation (In)		25 A
Equipment heat dissipation, current-dependent		8.78 W
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		70 °C
Ambient storage temperature - min		40 °C
Ambient storage temperature - max		70 °C
Design verification as per IEC/EN 61439		
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
Additional information		
Functions		System and cable protection

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Power circuit-breaker for trafo/generator/installation protection (EC000228)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Circuit breaker for power transformer, generator and system protection (ecl@ss13-27-37-04-09 [AJZ716018])		
Rated permanent current Iu	A	25
Rated voltage	V	690 - 690
Rated short-circuit breaking capacity Icu at 400 V, 50 Hz	kA	50
Overload release current setting	A	20 - 25
Adjustment range short-term delayed short-circuit release	A	0 - 0
Adjustment range undelayed short-circuit release	A	350 - 350
Power loss	W	8.8
Device construction		Built-in device fixed built-in technique
Integrated earth fault protection		No
Type of electrical connection of main circuit		Frame clamp
Suitable for DIN rail (top hat rail) mounting		No
DIN rail (top hat rail) mounting optional		Yes
Number of auxiliary contacts as normally closed contact		0
Number of auxiliary contacts as normally open contact		0
Number of auxiliary contacts as change-over contact		0
With switched-off indicator		No
With integrated under voltage release		No
Number of poles		3

Position of connection for main current circuit			Front side
Type of control element			Rocker lever
Complete device with protection unit			Yes
Motor drive integrated			No
Motor drive optional			No
Degree of protection (IP)			IP20