# Product data sheet

Specifications

## Circuit breaker, PowerPacT P, 600A, 3 pole, 600VAC, 18kA, I-Line, Micrologic 5.0, 100%, ABC

PGA36060CU33A

## Main

| | |
|---|---|
| **Range** | PowerPact |
| **product name** | PowerPact P |
| **Product or component type** | Circuit breaker |
| **Device application** | Distribution |

## Complementary

| | |
|---|---|
| **[In] rated current** | 600 A |
| **Number of Poles** | 3P |
| **control type** | Toggle |
| **Breaking capacity code** | G |
| **Breaking capacity** | AIR 65 kA 240 V AC 50/60 Hz UL 489<br>AIR 35 kA 480 V AC 50/60 Hz UL 489<br>AIR 18 kA 600 V AC 50/60 Hz UL 489<br>Icu 50 kA 240 V AC 50/60 Hz IEC 60947-2<br>Icu 35 kA 380/415 V AC 50/60 Hz IEC 60947-2 |
| **[Ue] rated operational voltage** | 600 V AC 50/60 Hz UL 489 |
| **Network frequency** | 50/60 Hz |
| **[Ics] rated service breaking capacity** | 25 kA 240 V AC 50/60 Hz IEC 60947-2<br>20 kA 380/415 V AC 50/60 Hz IEC 60947-2 |
| **[Uimp] rated impulse withstand voltage** | 8 kV IEC 60947-2 |
| **Trip unit technology** | Electronic, standard, MicroLogic 5.0, LSI |
| **Continuous current rating** | 100 % |
| **[Ui] rated insulation voltage** | 750 V IEC 60947-2 |
| **Trip unit name** | MicroLogic 5.0 |
| **AWG gauge** | 3 x AWG 3/0...500 kcmil aluminum/copper |
| **Local signalling** | Overload 1 1 LED amber)<br>1 trip indicator green) |
| **Mounting mode** | I-Line bracket) |
| **Mounting support** | Bracket |
| **Electrical connection** | I-Line connection, line<br>Lugs, load |
| **Terminal identifier** | AL800M23K |
| **Long time pick-up adjustment range** | 0.4...1 x Ir |
| **Mounting height** | 9 in (228.6 mm) |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| **Tightening torque** | 442.5 lbf.in (50 N.m) 0.1…0.4 in² (95…240 mm²) 3 x AWG 3/0...500 kcmil)<br>8.9…11.5 lbf.in (1.0…1.3 N.m) |
| **Number of slots** | 2 auxiliary switch OF plug-in)<br>1 alarm switch SD plug-in)<br>1 overcurrent trip switch SDE plug-in)<br>1 voltage release MN or MX plug-in) |
| **Power wire stripping length** | 1.0 in (25 mm) |
| **Height** | 12.86 in (326.64 mm) |
| **Width** | 8.27 in (210.06 mm) |
| **Depth** | 8.05 in (204.47 mm) |
| **Product weight** | 32 lb(US) (14.5 kg) |
| **Quantity per set** | 1 |
| **Phase connection** | ABC |
| **Circuit breaker application** | HACR rated |

# Environment

| | |
|---|---|
| **Quality labels** | CE |
| **Standards** | UL<br>CSA<br>NEMA<br>NOM-003-SCFI-2000<br>IEC 60947-2 |
| **Product certifications** | UL<br>CSA<br>NOM |
| **IP degree of protection** | Front cover IP40 |
| **Pollution degree** | 3 IEC 60947-1 |
| **Ambient air temperature for operation** | -13…158 °F (-25…70 °C) |
| **Ambient air temperature for storage** | -58…185 °F (-50…85 °C) |
| **Operating altitude** | < 2000 m without derating<br>4000 m with derating |

# Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Number of Units in Package 1** | 1 |
| **Package 1 Height** | 12.87 in (32.7 cm) |
| **Package 1 Width** | 8.27 in (21.0 cm) |
| **Package 1 Length** | 8.03 in (20.4 cm) |
| **Package 1 Weight** | 32.0001 lb(US) (14.515 kg) |

# Contractual warranty

| | |
|---|---|
| **Warranty** | 18 months |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

| | |
|---|---|
| Carbon footprint (kg CO2 eq, Total Life cycle) | 1857 |
| Environmental Disclosure | Product Environmental Profile |

## Use Better

### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | No |
| Packaging without single use plastic | No |
| EU RoHS Directive | Compliant with Exemptions |
| REACh Regulation | REACh Declaration |
| China RoHS Regulation | China RoHS declaration |
| PVC free | Yes |

## Use Again

### Repack and remanufacture

| | |
|---|---|
| Circularity Profile | End of Life Information |
| Removable battery | Yes |
| Take-back | No |