

# Product data sheet

Specifications



## auxiliary contact, TransferPacT, indication for source I and souce II



TPSAUX32

### Main

Range of product	TransferPacT
Product or component type	Auxiliary Contact Module
Device application	Signalling

### Complementary

Auxiliary contact composition	2 NO + 2 NC
Signalling function	Switch position (SI and SII)
Auxiliary connection terminal	Screw clamp terminal
Mounting mode	Clip-on
Mounting position	Right-angled
Tightening torque	0.6 N.m +/- 0.1 N.m
Height	90 mm
Width	17.5 mm
Depth	49.5 mm
Net weight	60 g
Accessory / separate part category	Signalling accessory

### Environment

IP degree of protection	IP20
Pollution degree	3

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.3 cm
Package 1 Width	5.8 cm
Package 1 Length	12.0 cm
Package 1 Weight	180.0 g
Unit Type of Package 2	S02

Number of Units in Package 2	18
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	3.5 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>

Recommended replacement(s)