Product data sheet

Specification





additional Input Output module, Altivar, 24V DC, 1 removable spring connector

VW3A3203

Product availability: Stock - Normally stocked in distribution facility

Price*: 198.00 USD

Main

Product or Component Type	Additional I/O module
Range Compatibility	Altivar Process ATV600 Altivar Machine ATV340 Altivar Process ATV900 Easy Altivar 610
Input/Output Type	analog input configurable voltage, current or probe discrete input discrete output
Analogue input number	2
Analogue input type	Al4, Al5 configurable current 020 mA/420 mA 01 ms 14 bits Al4, Al5 configurable voltage - 1010 V DC, 24 V max 20 kOhm 01 ms 14 bits Al4, Al5 configurable PTC, Pt 100, Pt 1000 01 ms 14 bits
Discrete output number	2
Discrete output type	DQ11, DQ12) assignable logic 1 ms
Discrete output logic	DQ11, DQ12) negative DQ11, DQ12) positive
Discrete input number	6
Discrete input type	DI11DI16) programmable 250 Ohm 1 ms
Discrete input logic	Negative DI11DI16) Positive DI11DI16)
Discrete input current	2.5 mA

Complementary

Discrete output voltage	24 V DC <= 30 V) assignable logic
Maximum output current	100 mA, assignable logic
Discrete input voltage	24 V DC <= 30 V)programmable
Electrical connection	Removable spring terminal block, 1.5 mm² / AWG 16
Protection type	Reverse polarity protection digital input Short-circuit protection output
Net Weight	1.1 lb(US) (0.5 kg)

Ordering and shipping details

Category	US1CP4E22206
Discount Schedule	CP4E
GTIN	3606480702525

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Returnability	Yes
Country of origin	ID

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.6 in (6.5 cm)
Package 1 Width	5.1 in (13.0 cm)
Package 1 Length	7.5 in (19.0 cm)
Package 1 Weight	5.8 oz (165.0 g)
Unit Type of Package 2	S03
Number of Units in Package 2	16
Package 2 Height	11.8 in (30.0 cm)
Package 2 Width	11.8 in (30.0 cm)
Package 2 Length	15.7 in (40.0 cm)
Package 2 Weight	7.425 lb(US) (3.368 kg)



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov