

Product datasheet

Specifications



RJ45 DATA OUTLET W/ SHUTTER White

X4045WH

Main

Range	Opale
Product or component type	Data socket
device presentation	Complete product
Cable shielding type	UTP
Data socket type	RJ45
Main colour tint	White
Type of packing	Flow-pack
Quantity per set	10

Complementary

Device mounting	Flush
Socket number	1
Communication network category	3
Connections - terminals	IDC
Cable stiffness	Rigid
Material	PC: front cover PA6: base cover
Fixing mode	Claws
Height	48 mm
Width	21 mm
Depth	35 mm
Rated current	15 A
Contact resistance	1 μ Ohm
Insulation resistance	\geq 100 MOhm
Dielectric strength	750 V
AWG gauge	AWG 26...AWG 22
Standards	ASTMD4566-98 TIA/EIA-568-B.2-1 TIA/EIA-568-B.2
Colour tint	White

Environment

IP degree of protection	IP20
-------------------------	------

Environmental characteristic	No UV resistant
Ambient air temperature for operation	-5...35 °C
Relative humidity	0...95 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.5 cm
Package 1 Width	4.5 cm
Package 1 Length	5 cm
Package 1 Weight	14 g

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Certifications & Standards

Eu Rohs Directive Compliant
[EU RoHS Declaration](#)

China Rohs Regulation [China RoHS declaration](#)
Pro-active China RoHS declaration (out of China RoHS legal scope)

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile No need of specific recycling operations
