

# Product data sheet

Specifications



Push button head, Harmony XAC, plastic, black, booted, operating travel 16mm, 40...+ 70 degree C

XACB9222

## Main

|                                 |  |
|---------------------------------|--|
| Range of product                | Harmony XAC                                  |
| Product or component type       | Head for push-button                         |
| Component name                  | XACB   |
| Marking                         | Unmarked                                     |
| Operator additional information | Booted                                       |
| Operating travel                | 16 mm  |
| Cap/Operator or lens colour     | Black  |
| Product compatibility           | XESD1191<br>XESD1281<br>XESD1181<br>XESD1291 |
| Sale per indivisible quantity   | 10   |

## Complementary

|                |          |
|----------------|----------|
| Product weight | 0.005 kg |
|----------------|----------|

## Environment

|                                       |  |
|---------------------------------------|--|
| Standards                             | IEC 60947-5-1<br>EN 60947-5-1<br>CSA C22.2 No 14   |
| Ambient air temperature for operation | -40...70 °C  |
| Ambient air temperature for storage   | -40...70 °C  |
| Vibration resistance                  | 15 gn (f= 10...500 Hz) conforming to IEC 60068-2-6 |
| Shock resistance                      | 100 gn conforming to IEC 60068-2-27                |
| Electrical shock protection class     | Class II conforming to IEC 61140                   |
| IP degree of protection               | IP65 conforming to IEC 60529                       |
| IK degree of protection               | IK08 conforming to EN 50102                        |

## Packing Units

|                              |     |
|------------------------------|-----|
| Unit Type of Package 1       | PCE |
| Number of Units in Package 1 | 1   |

|                              |          |
|------------------------------|----------|
| Package 1 Height             | 3.5 cm   |
| Package 1 Width              | 14.0 cm  |
| Package 1 Length             | 18.0 cm  |
| Package 1 Weight             | 6.0 g    |
| Unit Type of Package 2       | BAG      |
| Number of Units in Package 2 | 10       |
| Package 2 Height             | 3.5 cm   |
| Package 2 Width              | 18.0 cm  |
| Package 2 Length             | 14.0 cm  |
| Package 2 Weight             | 62.0 g   |
| Unit Type of Package 3       | S02      |
| Number of Units in Package 3 | 300      |
| Package 3 Height             | 15.0 cm  |
| Package 3 Width              | 30.0 cm  |
| Package 3 Length             | 40.0 cm  |
| Package 3 Weight             | 2.348 kg |

Offer Sustainability

|                            |  |
|----------------------------|--|
| REACH Regulation           | <a href="#">REACH Declaration</a>  |
| REACH free of SVHC         | Yes  |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a>  |
| Toxic heavy metal free     | Yes  |
| Mercury free               | Yes  |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a>   |
| RoHS exemption information | <a href="#">Yes</a>  |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |

Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Recommended replacement(s)