# Product data sheet Characteristics

## XU2S18PP340WD

Safety thru beam pair photo electric sensors, Preventa Safety detection, security light curtain XU2 S, of body, 750...1200 mm, 12...24 V

#### Main

Range of product	Telemecanique Safety light curtains XUSL
Product or component type	Safety thru-beam pair photo-electric sensors
Device short name	XU2S
Output type	1 safety outputs OSSD PNP
[Sn] nominal sensing distance	8 m

### Complementary

o impromornary		
Detection system	Transmitter-receiver system	
[Us] rated supply voltage	1224 V DC 1030 V reverse polarity protection	
Current consumption	<= 35 mA no-load	
Maximum voltage drop	<1.5 V (closed)	
Switching capacity in mA	<= 100 mA (overload and short-circuit protection)	
Switching frequency	500 Hz maximum	
Electrical connection	1 male connector M12 4 pins	
Line of sight type	90° to case axis	
Maximum delay response	1 ms	
Maximum delay recovery	1 ms	
Tightening torque	24 N.M fixing nut 2 N.m connector	
Function available	Built-in muting function Light or dark programmable switching	
Marking	CE	
Material	Nickel plated brass: case PMMA (polymethyl methacrylate): lenses	
Net weight	0.155 kg	

### **Environment**

Standards	EN/IEC 61496-2
Standards	EN/IEC 61496-1
	EN/IEC 60825-1
Safety level	Can reach PL = c associated with module XPSCM correctly wired conforming to EN/ISO 13849-1 Can reach category 2 associated with module XPSCM correctly wired conforming to EN/ISO 13849-1
	Type 2 conforming to IEC 61496-1-2
Ambient air temperature for operation	-2555 °C
Safety reliability data	PFH = 5.5E-7 1/h conforming to IEC 61508 with muting function PFH = 4.6E-7 1/h conforming to IEC 61508
Ambient air temperature for storage	-4070 °C
IP degree of protection	IP67 conforming to EN/IEC 60529
Shock resistance	30 gn 3 axes : 3 times conforming to EN/IEC 60068-2-27
Vibration resistance	7 gn (f= 1055 Hz) conforming to EN/IEC 60068-2-6

## Packing Units

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.2 cm
Package 1 Width	9.5 cm
Package 1 Length	13.0 cm
Package 1 Weight	165.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	22
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	4.077 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com
i or all reach rens enquines contact us at	3d3tdiridbiiity@tc3cfi3of3.com

### Contractual warranty

Warranty	18 months	